

AVAIL ADVANCED 1



SPECIFICATIES

| FRAME | |
|------------------|---|
| MATEN | XS, S, M, L |
| KLEUREN | Iron Rouge/Carbon/Chrome |
| FRAME | Advanced-grade composite, 12x142mm thru-axle, disc |
| VOORVORK | Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc |
| DEMPER | N/A |
| ONDERDELEN | |
| STUUR | Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm |
| HANDVATTEN | Liv Stratus Elite 2.0 |
| STUURPEN | Giant Contact AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm |
| ZADELPEN | Giant D-Fuse, composite, 14mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm |
| ZADEL | Liv Approach |
| AFMONTAGE | |
| SHIFTERS | Shimano 105 Di2 |
| VOORDERAILLEUR | Shimano 105 Di2 |
| ACHTERDERAILLEUR | Shimano 105 Di2 |
| REMMEN | Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F]160mm, [R]160mm |
| REMHENDELS | Shimano 105 Di2 |
| CASSETTE | Shimano 105, 12-speed, 11x36 |
| AANDRIJVING | KMC X12 |
| CRANKSET | Shimano 105, 34/50, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| WIELSET | |
|--------------------|---|
| VELGEN | Giant P-R1 Disc, alloy |
| NAVEN | Giant alloy, 12mm thru-axle |
| SPAKEN | Sapim |
| BANDEN | Giant Gavia Fondo 0, tubeless, 700x32c, folding |
| EXTRA'S | fender mount, tubeless prepared, 40mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 40mm |

Adviesprijs: € 3.599,00

GEOMETRIE

| FRAME | XS | S | M | L |
|---------------------------------|-------|-------|-------|-------|
| Zitbuis lengte (mm) | 405 | 435 | 465 | 495 |
| Zitbuis hoek | 74,5° | 74,5° | 74,0° | 74,0° |
| Frame Lengte (horizontaal) (mm) | 520 | 525 | 535 | 550 |
| Balhoofdbuis Lengte (mm) | 125 | 145 | 165 | 185 |
| Balhoofdbuis Hoek | 71,0° | 71,0° | 71,0° | 72,0° |
| Vork Sprong (mm) | 50 | 50 | 50 | 50 |
| Naloop (mm) | 68,3 | 68,3 | 68,3 | 61,8 |
| Wielbasis (mm) | 995 | 1002 | 1007 | 1013 |
| Liggende achtervork lengte (mm) | 420 | 420 | 420 | 420 |
| Bottom Bracket Drop (mm) | 75 | 75 | 75 | 75 |
| Stack (mm) | 528 | 547 | 566 | 589 |
| Reach (mm) | 373 | 373 | 373 | 381 |
| Stand Over Height (mm) | 712 | 737 | 762 | 789 |
| Stuur breedte (mm) | 380 | 400 | 400 | 420 |
| Stuurpen Lengte (mm) | 70 | 80 | 90 | 90 |
| Cranklengte (mm) | 165 | 165 | 170 | 172,5 |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.