

AVAIL ADVANCED 1



SPECS

CADRU	
MARIMI	XXS, XS, S, M, L
CULORI	Iron Rouge/Carbon/Chrome
CADRU	Advanced-grade composite, 12x142mm thru-axle, disc
FURCA	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
SOC	N/A
COMPONENTE	
GHIDON	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
PIPA	Giant Contact AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
TIJA SA	Giant D-Fuse, composite, 14mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SA	Liv Approach
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano 105 Di2
SCHIMBATOR FATA	Shimano 105 Di2
SCHIMBATOR SPATE	Shimano 105 Di2
FRANE	Shimano 105 Di2 hydraulic, Shimano SM-RT64 rotors, [F]160mm, [R]160mm
MANETE FRANA	Shimano 105 Di2
PINIOANE	Shimano 105, 12-speed, 11x36
LANT	KMC X12
ANGRENAJ	Shimano 105, 34/50, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

ROTI	
JANTE	Giant P-R1 Disc, alloy
BUTUCI	Giant alloy, 12mm thru-axle
SPITE	Sapim
ANVELOPE	Giant Gavia Fondo 0, tubeless, 700x32c, folding
EXTRAS	fender mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIE

CADRU	XXS	XS	S	M	L
Seat Tube Length (mm)	385	405	435	465	495
Seat Tube Angle	75,0°	74,5°	74,5°	74,0°	74,0°
Top Tube Length (mm)	500	520	525	535	550
Head Tube Length (mm)	110	125	145	165	185
Head Tube Angle	69,8°	71,0°	71,0°	71,0°	72,0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	76,2	68,3	68,3	68,3	61,8
Wheelbase (mm)	989	995	1002	1007	1013
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	75	75
Stack (mm)	510	528	547	566	589
Reach (mm)	363	373	373	373	381
Stand Over Height (mm)	683	712	737	762	789
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	160	165	165	170	172,5

Toate specificatiile enumerate se pot schimba fara notificare prealabila.