



## ŠPECIFIKÁCIE

| RÁM               |  |
|-------------------|--|
| VELKOSTI          | XXS, XS, S, M, L   |
| FARBY             | Mechanic Rose  |
| RÁM               | Advanced-grade composite, 12x142mm thru-axle, disc                                       |
| VIDLICA           | Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc     |
| TLMIČ             | N/A  |
| KOMPONENTY        |  |
| RIADIDLÁ          | Liv Contact SL D-Fuse, 31.8mm XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm        |
| GRIPY             | Liv Stratus Elite 2.0  |
| PREDSTAVEC        | Giant Contact AeroLight XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm                   |
| SEDLOVKA          | Giant D-Fuse, composite, 14mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm |
| SEDADLO           | Liv Approach   |
| PEDÁLE            | platform pedal [GCS,GTS] N/A [all other GSC]   |
| POHON             |  |
| RADENIE           | Shimano 105 Di2  |
| PREŠMYKAČ         | Shimano 105 Di2  |
| PREHADZOVAČKA     | Shimano 105 Di2  |
| BRZDY             | Shimano 105 Di2 hydraulic, Shimano RT-MT800 rotors [F]160mm, [R]160mm                    |
| BRZDOVÉ PÁKY      | Shimano 105 Di2  |
| KAZETA            | Shimano 105, 12-speed, 11x36   |
| REŤAZ             | KMC X12  |
| KLUKY             | Shimano 105, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm                 |
| STREDOVÉ ZLOŽENIE | Shimano, press fit   |

| KOLESÁ                    |  |
|---------------------------|--|
| RÁFIKY                    | Giant P-R2 Disc wheelset, alloy                                      |
| NÁBOJE                    | Giant alloy, 12mm thru-axle  |
| ŠPICE                     | Sapim  |
| PNEUMATIKY                | Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding             |
| DOPLNKY                   | two bottle cage, fender mount, tubeless prepared, 40mm max tire size |
| LIMITY                    |  |
| MAXIMÁLNA ŠÍRKA PNEUMATÍK | 40mm   |

Cena: 3 749 €

## GEOMETRIA

| RÁM  | XXS   | XS    | S     | M     | L     |
|--|-------|-------|-------|-------|-------|
| Dĺžka sedlovej trubky (mm)                       | 385   | 405   | 435   | 465   | 495   |
| Uhol sedlovej trubky                             | 75,0° | 74,5° | 74,5° | 74,0° | 74,0° |
| Dĺžka hornej rámovej trubky (mm)                 | 500   | 520   | 525   | 535   | 555   |
| Dĺžka hlavovej trubky (mm)                       | 110   | 125   | 145   | 165   | 185   |
| Uhol hlavovej trubky                             | 69,8° | 71,0° | 71,0° | 71,0° | 72,0° |
| Offset vidlice (mm)                              | 50    | 50    | 50    | 50    | 50    |
| Trail (mm)                                       | 76    | 68    | 68    | 68    | 61    |
| Rázvor (mm)                                      | 989   | 995   | 1002  | 1007  | 1013  |
| Dĺžka zadnej stavby (mm)                         | 420   | 420   | 420   | 420   | 420   |
| Rozdiel zadnej voči stredovej osi - BB DROP (mm) | 75    | 75    | 73    | 73    | 73    |
| Stack - výška riadenia (mm)                      | 510   | 528   | 547   | 566   | 589   |
| StackToHandlebar (mm)                            | 588   | 606   | 626   | 647   | 668   |
| Reach (mm)                                       | 363   | 373   | 373   | 373   | 381   |
| ReachToHandlebar (mm)                            | 408   | 420   | 429   | 439   | 449   |
| Výška rámu od zeme (mm)                          | 683   | 712   | 737   | 762   | 789   |
| Šírka riaditok (mm)                              | 380   | 380   | 400   | 400   | 420   |
| Dĺžka predstavca (mm)                            | 70    | 70    | 80    | 90    | 90    |
| Dĺžka klúku (mm)                                 | 165   | 165   | 170   | 170   | 172,5 |
| Rozmer kolies                                    | 700C  | 700C  | 700C  | 700C  | 700C  |

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.