



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	XXS, XS, S, M, L
BARVE	Mechanic Rose
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc
VILICE	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Liv Contact SL D-Fuse, 31.8mm XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
OPORA KRMILA	Giant Contact AeroLight XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
OPORA SEDEŽA	Giant D-Fuse, composite, 14mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SEDEŽ	Liv Approach
PEDALA	platform pedal [GCS,GTS] N/A [all other GSC]
POGON	
PRESTAVNE ROČICE	Shimano 105 Di2
PREDNJI MENJALNIK	Shimano 105 Di2
ZADNJI MENJALNIK	Shimano 105 Di2
ZAVORE	Shimano 105 Di2 hydraulic, Shimano RT-MT800 rotors [F]160mm, [R]160mm
ZAVORNE ROČICE	Shimano 105 Di2
VERIŽNIK	Shimano 105, 12-speed, 11x36
VERIGA	KMC X12
GONILKE Z VERIŽNIKI	Shimano 105, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant P-R2 Disc wheelset, alloy
PESTA	Giant alloy, 12mm thru-axle
NAPERE	Sapim
PLAŠČI	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
DODATKI	two bottle cage, fender mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

## GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dolžina sedežne cevi (mm)	385	405	435	465	495
Kot sedežne cevi	75,0°	74,5°	74,5°	74,0°	74,0°
Top Tube Length (mm)	500	520	525	535	555
Višina glave okvirja (mm)	110	125	145	165	185
Krmlni kot	69,8°	71,0°	71,0°	71,0°	72,0°
Zamik vpetja osi (mm)	50	50	50	50	50
Trail (mm)	76	68	68	68	61
Medosna razdalja (mm)	989	995	1002	1007	1013
Dolžina cevi ob verigi (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	73	73	73
Oddaljenost zgornje cevi od gonilne osi (mm)	510	528	547	566	589
StackToHandlebar (mm)	588	606	626	647	668
Doseg (mm)	363	373	373	373	381
ReachToHandlebar (mm)	408	420	429	439	449
Višina zgornje cevi (mm)	683	712	737	762	789
Širina krmila (mm)	380	380	400	400	420
Dolžina opore krmila (mm)	70	70	80	90	90
Dolžina gonilke (mm)	165	165	170	170	172,5
Velikost obročnikov	700C	700C	700C	700C	700C

Vse navedene specifikacije se lahko spremenijo brez obvestila.