

# AVAIL ADVANCED 1



## SPECS

RAM	
STORLEKAR	XXS, XS, S, M, L
FÄRGER	Mechanic Rose
RAM	Advanced-grade composite, 12x142mm thru-axle, disc
GAFFEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
BAKDÄMPARE	N/A
KOMPONENTER	
STYRE	Liv Contact SL D-Fuse, 31.8mm XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GREPPAR	Liv Stratus Elite 2.0
STAM	Giant Contact AeroLight XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SADELSTOLPE	Giant D-Fuse, composite, 14mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADEL	Liv Approach
PEDALER	platform pedal [GCS,GTS] N/A [all other GSC]
DRIVLINA	
VÄXLAR	Shimano 105 Di2
FRAMVÄXEL	Shimano 105 Di2
BAKVÄXEL	Shimano 105 Di2
BROMSAR	Shimano 105 Di2 hydraulic, Shimano RT-MT800 rotors [F]160mm, [R]160mm
BROMSSPAKAR	Shimano 105 Di2
KASSETT	Shimano 105, 12-speed, 11x36
KEDJA	KMC X12
VEVPARTI	Shimano 105, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BROMSREGLAGE	Shimano, press fit

HJUL	
FÄLGAR	Giant P-R2 Disc wheelset, alloy
NAV	Giant alloy, 12mm thru-axle
EKRAR	Sapim
DÄCK	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAFUNKTIONER	two bottle cage, fender mount, tubeless prepared, 40mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	40mm

Price: 42 390,00 kr

## GEOMETRY

RAM	M	L
Längd sadelrör (mm)	465	495
Vinkel sadelrör	74,0°	74,0°
Topprörets längd (mm)	535	555
Styrhuvud Längd (mm)	165	185
Vinkel styrhuvud	71,0°	72,0°
Gaffelvinkel (mm)	50	50
Spår (mm)	68	61
Hjulbas (mm)	1007	1013
Kedjestagslängd (mm)	420	420
Nedre fäste Drop (mm)	73	73
Stack (mm)	566	589
StackToHandlebar (mm)	647	668
Reach (mm)	373	381
ReachToHandlebar (mm)	439	449
Stå över höjden (mm)	762	789
Styrets bredd (mm)	400	420
Stamlängd (mm)	90	90
Vevlängd (mm)	170	172,5
Hjulstorlek	700C	700C

All specifications listed are subject to change without notice.