## **AVAIL ADVANCED 2**





## **SPECS**

FRAME				
SIZES	XS, S, M			
COLOURS	Moonstone/Gray/Chrome			
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc			
FORK	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc			
sноск	N/A			
COMPONENTS				
HANDLEBAR	Liv Contact SL D-Fuse, 31.8mm XS:38/41cm, S:40/43cm, M:40/43cm			
GRIPS	Liv Stratus Elite 2.0			
STEM	Giant Contact Aerolight XS:70mm, S:80mm, M:90mm			
SEATPOST	Giant D-Fuse, composite, 14mm offset			
SADDLE	Liv Approach			
PEDALS	N/A			
DRIVETRAIN				
SHIFTERS	Shimano 105			
FRONT DERAILLEUR	Shimano 105			
REAR DERAILLEUR	Shimano 105			
BRAKES	Shimano 105 hydraulic, Shimano SM-RT64 rotors, [F]160mm, [R]160mm			
BRAKE LEVERS	Shimano 105			
CASSETTE	Shimano 105, 12-speed, 11x36			
CHAIN	KMC 12			
CRANKSET	Shimano 105, 34/50 XS:165mm, S:165mm, M:170mm			
BOTTOM BRACKET	Shimano, press fit			

WHEELS	
RIMS	Giant P-R1, [F]30mm, [R]30mm
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	Water bottle cages, tubeless prepared, 38mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	38mm

Price: \$3,799.00

## **GEOMETRY**

FRAME	XS	S	M
Seat Tube Length (mm)	405	435	465
Seat Tube Angle	74.5°	74.5°	74.0°
Top Tube Length (mm)	520	525	535
Head Tube Length (mm)	125	145	165
Head Tube Angle	71.0°	71.0°	71.0°
Fork Rake (mm)	50	50	50
Trail (mm)	68.3	68.3	68.3
Wheelbase (mm)	995	1002	1007
Chain Stay Length (mm)	420	420	420
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	528	547	566
Reach (mm)	373	373	373
Stand Over Height (mm)	712	737	762
Stem Length (mm)	70	80	90
Crank Length (mm)	165	170	170

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.