

AVAIL ADVANCED 2



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Moonstone/Gray/Chrome, RosyBrown/OceanStorm
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced-grade Composite, full-composite OverDrive steerer, 12x100mm thru-axle, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SEATPOST	Giant D-Fuse, composite, 14mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADDLE	Liv Approach
DRIVETRAIN	
SHIFTERS	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 hydraulic, Shimano SM-RT64 rotors, [F]160mm, [R]160mm
BRAKE LEVERS	Shimano 105
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC 12
CRANKSET	Shimano 105, 34/50, XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant P-R1 Disc, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 1, tubeless, 700x32c, folding
EXTRAS	fender mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

Recommended Retail Price: \$3,300.00

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (inch)	15.2	15.9	17.1	18.3	19.5
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°	74.0°
Top Tube Length (inch)	19.7	20.5	20.7	21.1	21.7
Head Tube Length (inch)	4.3	4.9	5.7	6.5	7.3
Head Tube Angle	69.8°	71.0°	71.0°	71.0°	72.0°
Fork Rake (inch)	2	2	2	2	2
Trail (inch)	3	2.7	2.7	2.7	2.4
Wheelbase (inch)	38.9	39.2	39.4	39.6	39.9
Chain Stay Length (inch)	16.5	16.5	16.5	16.5	16.5
Bottom Bracket Drop (inch)	3	3	3	3	3
Stack (inch)	20.1	20.8	21.5	22.3	23.2
Stack to handlebar (inch)	23.1	23.9	24.6	25.5	26.3
Reach (inch)	14.3	14.7	14.7	14.7	15
Reach to handlebar (inch)	16.1	16.5	16.9	17.3	17.7
Stand Over Height (inch)	26.9	28	29	30	31.1
Handlebar Width (inch)	15	15	15.7	15.7	16.5
Stem Length (inch)	2.8	2.8	3.1	3.5	3.5
Crank Length (inch)	6.3	6.5	6.5	6.7	6.8

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*