# AVAIL ADVANCED E+ ELITE 0



## SPECIFIKATIONER

| | |
|---|---|
| **E+ SYSTEM** | |
| **MOTOR** | SyncDrive Move Plus, Hub drive 75Nm max |
| **KONTROLLER** | Mode support switch from SRAM bonus button |
| **DISPLAY** | Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display |
| **BATTERI** | Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible |
| **LADER** | Giant EnergyPak 4A smart charger, 60% in 1:45 |
| **FORBINDELSE** | Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile |
| **RAMME** | |
| **STØRRELSER** | XS, S, M, L |
| **FARVER** | Moonstone |
| **RAMME** | Advanced-grade composite,12x145 thru-axle |
| **FORGAFFEL** | Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc |
| **BAGDÆMPER** | - |
| **KOMPONENTER** | |
| **STYR** | Liv Contact SLR D-Fuse 31.8 carbon |
| **FREMPIND** | Contact SLR Aerolight 31.8 carbon |
| **SADELPIND** | Giant D-Fuse SLR, Composite, -5/+15mm offset |
| **SADEL** | Liv Alacra SL CS |
| **GEARGRUPPE** | |
| **SKIFTEGREB** | Sram RED AXS |
| **FORSKIFTER** | Sram RED AXS |
| **BAGSKIFTER** | Sram RED AXS |
| **BREMSER** | Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R] |
| **BREMSEGREB** | Sram RED AXS HRD |
| **KASSETTE** | SRAM RED XG-1290 10x33T 12-speed |
| **KÆDE** | Sram RED 12-speed |
| **KRANKSÆT** | Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS |
| **KRANKBOKS** | Giant E+ System BBSS |

| | |
|---|---|
| **HJUL** | |
| **FÆLGE** | Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized |
| **DÆK** | Cadex Race GC, tubeless, 700x30, folding |
| **EKSTRA** | Fender adapter |
| **TILBEHØR** | |
| **LYGTER** | Seatpost clamp integrated tail light |

**Pris: 82.999,00 kr.**

## GEOMETRI

| RAMME | XS | S | M | L |
|---|---|---|---|---|
| Sadelrørslængde (mm) | 400 | 435 | 470 | 505 |
| Sadelrørsvinkel | 74,5° | 74,5° | 74,0° | 73,5° |
| Overrørslængde (mm) | 515 | 525 | 540 | 555 |
| Kronrørslængde (mm) | 120 | 135 | 155 | 175 |
| Kronrørsvinkel | 70,5° | 71,0° | 72,0° | 72,0° |
| Forgaffel fremspring (rake) (mm) | 50 | 50 | 50 | 50 |
| Akselafstand (mm) | 993 | 999 | 1003 | 1013 |
| Kædestagslængde (mm) | 420 | 420 | 420 | 420 |
| Krankboks drop (mm) | 80 | 80 | 80 | 75 |
| Stack (mm) | 529 | 545 | 563 | 582 |
| Reach (mm) | 368 | 374 | 378 | 382 |
| Skridthøjde (mm) | 677 | 708 | 743 | 782 |
| Styrbredde (mm) | 380 | 400 | 400 | 420 |
| Frempindslængde (mm) | 80 | 90 | 100 | 110 |
| Hjulstørrelse | 700C | 700C | 700C | 700C |

*Alle de anførte specifikationer kan ændres uden varsel.*