

# AVAIL ADVANCED E+ ELITE 0



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	SyncDrive Move Plus, 75Nm (effective)
<b>CONTROLLER</b>	Mode support switch from SRAM bonus button
<b>DISPLAY</b>	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
<b>BATTERY</b>	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
<b>CHARGER</b>	Giant EnergyPak 4A smart charger, 60% in 1:45
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Gloss Raw Carbon / Matte Raw Carbon
<b>FRAME</b>	Advanced-grade composite, 12x145 thru-axle
<b>FORK</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
<b>SHOCK</b>	-
COMPONENTS	
<b>HANDLEBAR</b>	Liv Contact SLR D-Fuse 31.8 carbon
<b>STEM</b>	Contact SLR Aerolight 31.8 carbon
<b>SEATPOST</b>	Giant D-Fuse SLR, Composite, -5/+15mm offset
<b>SADDLE</b>	Liv Alacra SL CS
<b>PEDALS</b>	-
DRIVETRAIN	
<b>SHIFTERS</b>	Sram RED AXS
<b>FRONT DERAILLEUR</b>	Sram RED AXS
<b>REAR DERAILLEUR</b>	Sram RED AXS
<b>BRAKES</b>	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
<b>BRAKE LEVERS</b>	Sram RED AXS HRD
<b>CASSETTE</b>	SRAM RED XG-1290 10x33T 12-speed
<b>CHAIN</b>	Sram RED 12-speed
<b>CRANKSET</b>	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Carbon ISIS
<b>BOTTOM BRACKET</b>	Giant E+ System BBSS

WHEELS	
<b>RIMS</b>	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle
<b>SPOKES</b>	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
<b>TIRES</b>	Cadex Classic 95PSI 700x28C 170TPI Tubeless Foldable
ACCESSORIES	
<b>LIGHTING</b>	Seatpost clamp integrated tail light

**Suggested Retail Price (CDN): \$14,999.00**

## FRAME GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	400	435	470
Seat Tube Angle	74.5°	74.5°	74.0°
Top Tube Length (mm)	515	525	540
Head Tube Length (mm)	120	135	155
Head Tube Angle	70.5°	71.0°	72.0°
Fork Rake (mm)	50	50	50
Trail (mm)	72	68.3	61.8
Wheelbase (mm)	993	999.2	1003
Chain Stay Length (mm)	420	420	420
Bottom Bracket Drop (mm)	80	80	80
Stack (mm)	528.9	545	562.8
Reach (mm)	368	373.6	378.4
Stand Over Height (mm)	677	708	743
Handlebar Width (mm)	380	400	400
Stem Length (mm)	80	90	100
Crank Length (mm)	165	165	170
Wheel Size	700C	700C	700C

*All prices and specifications are subject to change without notice.*