AVAIL ADVANCED E+ ELITE 0



TEKNISET TIEDOT

E+ SYSTEM	
MOOTTORI	SyncDrive Move Plus, Hub drive 75Nm max
OHJAUSYKSIKKÖ	Mode support switch from SRAM bonus button
NÄYTTÖ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
AKKU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LATURI	Giant EnergyPak 4A smart charger, 60% in 1:45
YHTEYDET MUIHIN LAITTEISIIN	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
RUNKO	
KOOT	XS, S, M, L
VÄRIT	Moonstone
RUNKO	Advanced-grade composite,12x145 thru-axle
HAARUKKA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
ISKUNVAIMENNIN	-
KOMPONENTIT	
OHJAUSTANKO	Liv Contact SLR D-Fuse 31.8 carbon
OHJAINKANNATIN	Contact SLR Aerolight 31.8 carbon
SATULATOLPPA	Giant D-Fuse SLR, Composite, -5/+15mm offset
SATULA	Liv Alacra SL CS
VOIMANSIIRTO	
VAIHDEVIPU	Sram RED AXS
ETUVAIHTAJA	Sram RED AXS
TAKAVAIHTAJA	Sram RED AXS
JARRUT	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
JARRUKAHVAT	Sram RED AXS HRD
RATASPAKKA	SRAM RED XG-1290 10x33T 12-speed
KETJUT	Sram RED 12-speed
KAMPISARJA	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
KESKIÖ	Giant E+ System BBSS

RENKAAT	
VANTEET	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
RENKAAT	Cadex Race GC, tubeless, 700x30, folding
LISÄTIEDOT	Fender adapter
TARVIKKEET	
VALOT	Seatpost clamp integrated tail light

Suositushinta: 11 199,00 €

GEOMETRIA

RUNKO	XS	S	M	L
Satulaputken pituus (mm)	400	435	470	505
Satulaputken kulma	74,5°	74,5°	74,0°	73,5°
Vaakaputken pituus (mm)	515	525	540	555
Emäputken pituus (mm)	120	135	155	175
Emäputken kulma	70,5°	71,0°	72,0°	72,0°
Haarukan offset (mm)	50	50	50	50
Akseliväli (mm)	993	999	1003	1013
Takahaarukan alaputken pituus (mm)	420	420	420	420
Keskiön pudotus (mm)	80	80	80	75
Stack-mitta (mm)	529	545	563	582
Reach-mitta (mm)	368	374	378	382
Standover-mitta (mm)	677	708	743	782
Ohjaustangon leveys (mm)	380	400	400	420
Ohjainkannattimen pituus (mm)	80	90	100	110
Rengaskoko	700C	700C	700C	700C

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.