AVAIL ADVANCED E+ ELITE 0

SPECIFICATIES

E+ SYSTEM	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
BEDIENINGSUNIT	Mode support switch from SRAM bonus button
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
ACCU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	XS, S, M, L
KLEUREN	Moonstone
FRAME	Advanced-grade composite,12x145 thru-axle
VOORVORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
DEMPER	-
ONDERDELEN	
STUUR	Liv Contact SLR D-Fuse 31.8 carbon
STUURPEN	Contact SLR Aerolight 31.8 carbon
ZADELPEN	Giant D-Fuse SLR, Composite, -5/+15mm offset
ZADEL	Liv Alacra SL CS
AFMONTAGE	
SHIFTERS	Sram RED AXS
VOORDERAILLEUR	Sram RED AXS
ACHTERDERAILLEUR	Sram RED AXS
REMMEN	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
REMHENDELS	Sram RED AXS HRD
CASSETTE	SRAM RED XG-1290 10x33T 12-speed
AANDRIJVING	Sram RED 12-speed
CRANKSET	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WIELSET	
VELGEN	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
BANDEN	Cadex Race GC, tubeless, 700x30, folding
EXTRA'S	Fender adapter
ACCESSORES	
VERLICHTING	Seatpost clamp integrated tail light

Adviesprijs: € 10.499,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis Lengte (mm)	400	435	470	505
Zitbuis Hoek	74,5°	74,5°	74,0°	73,5°
Frame Lengte (horizontaal) (mm)	515	525	540	555
Balhoofdbuis Lengte (mm)	120	135	155	175
Balhoofdbuis Hoek	70,5°	71,0°	72,0°	72,0°
Vork Sprong (mm)	50	50	50	50
Wielbasis (mm)	993	999	1003	1013
Liggende achtervork lengte (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	80	75
Stack (mm)	529	545	563	582
Reach (mm)	368	374	378	382
Stand Over Height (mm)	677	708	743	782
Stuur breedte (mm)	380	400	400	420
Stuurpen Lengte (mm)	80	90	100	110
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.