AVAIL ADVANCED E+ ELITE 0



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
SENSOR	Mode support switch from SRAM bonus button
PRIKAZ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERIJA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	XS, S, M, L
BOJE	Moonstone
OKVIR	Advanced-grade composite,12x145 thru-axle
VILICA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMORTIZER	-
KOMPONENTE	
VOLAN	Liv Contact SLR D-Fuse 31.8 carbon
LULA VOLANA	Contact SLR Aerolight 31.8 carbon
CIJEV SJEDALA	Giant D-Fuse SLR, Composite, -5/+15mm offset
SJEDALO	Liv Alacra SL CS
POGON	
RUČICE MJENJAČA	Sram RED AXS
PREDNJI MJENJAČ	Sram RED AXS
STRAŽNJI MJENJAČ	Sram RED AXS
KOČNICE	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
RUČICE KOČNICA	Sram RED AXS HRD
KAZETA	SRAM RED XG-1290 10x33T 12-speed
LANAC	Sram RED 12-speed
POGON	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
OSOVINA POGONA (BB)	Giant E+ System BBSS

KOTAČI	
OBRUČI	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
GUME	Cadex Race GC, tubeless, 700x30, folding
DODACI	Fender adapter
DODACI	
SVJETLA	Seatpost clamp integrated tail light

GEOMETRIJA

OKVIR	XS	S	M	L
Dužina cijevi sjedala (mm)	400	435	470	505
Kut cijevi sjedala	74,5°	74,5°	74,0°	73,5°
Dužina gornje cijevi (mm)	515	525	540	555
Dužina prednje cijevi (mm)	120	135	155	175
Kut vilice	70,5°	71,0°	72,0°	72,0°
Zakrivljenost vilice (offset) (mm)	50	50	50	50
Međuosovinski razmak kotača (mm)	993	999	1003	1013
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	420	420	420	420
Položaj osovine pogona (mm)	80	80	80	75
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	529	545	563	582
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	368	374	378	382
Prekoračna visina (mm)	677	708	743	782
Širina volana (mm)	380	400	400	420
Dužina lule volana (mm)	80	90	100	110
Veličina kotača	700C	700C	700C	700C

Sve navedene specifikacije podložne su promjeni bez prethodne najave.