

AVAIL ADVANCED E+ ELITE 0



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	SyncDriveMove Plus Hub drive 30 Nm (75 Nm effective)
COMANDO	Mode support switch from SRAM bonus button
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARICATORE	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNETTIVITÀ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
TELAIO	
TAGLIE	XS, S, M, L
COLORAZIONI	Gloss Raw Carbon / Matte Raw Carbon
TELAIO	Advanced-grade composite, 12x145 thru-axle
FORCELLA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMMORTIZZATORE	-
COMPONENTISTICA	
MANUBRIO	Liv Contact SLR D-Fuse 31.8 carbon
ATTACCO MANUBRIO	Contact SLR Aerolight 31.8 carbon
REGGISSELLA	Giant D-Fuse SLR, Composite, -5/+15mm offset
SELLA	Liv Alacra SL CS
PEDALI	-
SISTEMA DI TRASMISSIONE	
CAMBIO	Sram RED AXS
DERAGLIATORE ANTERIORE	Sram RED AXS
DERAGLIATORE POSTERIORE	Sram RED AXS
FRENI	Sram RED AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
COMANDI FRENO	Sram RED AXS HRD
PACCO PIGNONI	SRAM RED XG-1290 10x33T 12-speed
CATENA	Sram RED 12-speed
GUARNITURA	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Carbon ISIS
MOVIMENTO CENTRALE	Giant E+ System BBSS

RUOTE	
CERCHI	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle
RAGGI	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
COPERTONI	Cadex Classic 95PSI 700x28C 170TPI Tubeless Foldable
ACCESSORI	
ILLUMINAZIONE	Seatpost clamp integrated tail light

Prezzo: € 10.499

GEOMETRIA

TELAIO	XS	S	M	L
Lunghezza Tubo Sella (mm)	400	435	470	505
Angolo Tubo Sella	74,5°	74,5°	74,0°	73,5°
Lunghezza Tubo Orizzontale (mm)	515	525	540	555
Lunghezza Tubo Sterzo (mm)	120	135	155	175
Angolo Sterzo	70,5°	71,0°	72,0°	72,0°
Rake Forcella (mm)	50	50	50	50
Avancorsa (mm)	72	68,3	61,8	61,8
Interasse (mm)	993	999,2	1003	1013,2
Lunghezza Carro Posteriore (mm)	420	420	420	420
Drop Movimento Centrale (mm)	80	80	80	75
Stack (mm)	528,9	545	562,8	582,4
Reach (mm)	368	373,6	378,4	382,4
Altezza stand over (mm)	677	708	743	782,4
Larghezza Manubrio c/c (mm)	380	400	400	420
Lunghezza Attacco Manubrio (mm)	80	90	100	110
Lunghezza Pedivella (mm)	165	165	170	172,5
Dimensione Ruote	700C	700C	700C	700C

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.