

AVAIL ADVANCED E+ ELITE 1



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
MANDO	Mode support switch from SRAM Blips
PANTALLA	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERÍA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARGADOR	Giant EnergyPak 4A smart charger, 60% in 1:45
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	XS, S, M, L
COLORES	Ice Age / Carbon smoke
CUADRO	Advanced-grade composite, 12x145 thru-axle
HORQUILLA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMORTIGUADOR	-
COMPONENTES	
MANILLAR	Liv Contact SLR D-Fuse 31.8 carbon
POTENCIA	Contact SLR Aerolight 31.8 carbon
TIJA DE SILLÍN	Giant D-Fuse SL, Composite, 16mm offset
SILLÍN	Liv Alacra SL CS
PEDALES	-
TRANSMISIÓN	
MANETAS DE CAMBIO	Sram Force AXS
DESVIADOR	Sram Force AXS
CAMBIO TRASERO	Sram Force AXS
FRENOS	Sram Force AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
PALANCAS DE FRENOS	Sram Force AXS HRD
CASETTE	SRAM Force XG-1270 10x33T 12-speed
CADENA	Sram Force 12-speed
JGO. PLATOS Y BIELAS	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Carbon ISIS
CAJA DE PEDALIER	Giant E+ System BBSS

RUEDAS	
LLANTAS	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle
RADIOS	Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
CUBIERTAS	Cadex Classic 75PSI 700x32C 170TPI Tubeless Foldable
ACCESORIOS	
LUCES	Seatpost clamp integrated tail light

Precio: 7.999,00 €

GEOMETRÍA

CUADRO	XS	S	M
Longitud del tubo del sillín (mm)	400	435	470
Ángulo del tubo del sillín	74,5°	74,5°	74,0°
Longitud del tubo superior (mm) (mm)	515	525	540
Longitud del tubo de dirección (mm) (mm)	120	135	155
Ángulo del tubo de dirección	70,5°	71,0°	72,0°
Inclinación de la horquilla (mm)	50	50	50
Trail (mm) (mm)	72	68,3	61,8
Distancia entre ejes (mm) (mm)	993	999,2	1003
Longitud de la vaina (mm) (mm)	420	420	420
Caída del eje de pedalier (mm) (mm)	80	80	80
Stack (mm) (mm)	528,9	545	562,8
Reach (mm) (mm)	368	373,6	378,4
Altura del suelo al tubo (mm) (mm)	677	708	743
Ancho del manillar (mm) (mm)	380	400	400
Longitud de la potencia (mm) (mm)	80	90	100
Longitud de las bielas (mm) (mm)	165	165	170
Tamaño de ruedas	700C	700C	700C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.