

AVAIL ADVANCED E+ ELITE 1



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
SENSOR	Mode support switch from SRAM bonus button
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERÍA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONECTIVIDAD	Giant RideControl App enabled, ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	XS, S, M, L
COLORES	Dreamy Blue
CUADRO	Advanced-grade composite, 12x145 thru-axle
TIJERA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMORTIGUADOR	-
COMPONENTES	
MANUBRIO	Liv Contact SLR D-Fuse 31.8 carbon
POTENCIA	Contact SLR Aerolight 31.8 carbon
POSTE DE ASIENTO	Giant D-Fuse SL, Composite, 16mm offset
ASIENTO	Liv Alacra SL CS
TRANSMISIÓN	
MANETAS DE CAMBIO	Sram Force AXS
DESVIADOR	Sram Force AXS
CAMBIO TRASERO	Sram Force AXS
FRENOS	Sram Force AXS HRD, Centerline 160mm center-lock [F] 160mm 6-bols [R]
PALANCAS DE FRENOS	Sram Force AXS HRD
CASSETTE	SRAM Force XG-1270 10x33T 12-speed
CADENA	Sram Force 12-speed
MULTIPLICACIÓN	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Carbon ISIS
EJE DE CENTRO	Giant E+ System BBSS

RUEDAS	
RUEDAS	Giant SLR 1 E+ 36 Carbon Disc Wheel System, Hookless, Tubeless Ready, 12mm thru-axle, w/ Sapim spoke E-Light [R] CX-Ray [F], e-bike optimized
NEUMÁTICOS	Cadex Classic, tubeless, 700x32, folding
EXTRAS	Fender adapter
ACCESORIOS	
LUCES	Seatpost clamp integrated tail light

Precio: \$189,990.00

GEOMETRÍA

CUADRO	XS	S	M
Longitud de la Base del Poste de Asiento (mm)	400	435	470
Ángulo de la Base del Poste de Asiento	74.5°	74.5°	74.0°
Longitud del Tubo Superior (mm)	515	525	540
Longitud del Telescopio (mm)	120	135	155
Ángulo del Telescopio	70.5°	71.0°	72.0°
Rake (mm)	50	50	50
Distancia entre Ejes (mm)	993	999	1003
Longitud de Vaina Inferior (mm)	420	420	420
Caída del Eje de Centro (mm)	80	80	80
Stack (mm)	529	545	563
Reach (mm)	368	374	378
Altura del Tubo Superior al Suelo (mm)	677	708	743
Ancho del Manubrio (mm)	380	400	400
Longitud de la Potencia (mm)	80	90	100
Tamaño de las Ruedas	700C	700C	700C

Todas las especificaciones están sujetas a cambios sin previo aviso.