

AVAIL ADVANCED E+ ELITE 2



SPECIFIKATIONER

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
KONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERI	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
LADER	Giant EnergyPak smart charger 4A
FORBINDELSE	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAMME	
STØRRELSER	XS, S, M, L
FARVER	Iron Rouge/ Carbon Smoke
RAMME	Advanced-grade composite, 12x145 thru-axle
FORGAFFEL	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
BAGDÆMPER	-
KOMPONENTER	
STYR	Liv Contact SL D-Fuse 31.8 alloy
FREMPIND	Contact SL Aerolight 31.8 alloy
SADELPIND	Giant D-Fuse, Composite, 14mm offset
SADEL	Liv Approach
GEARGRUPPE	
SKIFTEGREB	Sram Rival AXS
FORSKIIFTER	Sram Rival AXS
BAGSKIIFTER	Sram Rival AXS
BREMSE	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
BREMSEGREB	Sram Rival AXS HRD
KASSETTE	Sram Rival XG-1250 10x36T 12-speed
KÆDE	Sram Rival 12-speed
KRANKSÆT	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS"
KRANKBOKS	Giant E+ System BBSS

HJUL	
FÆLGE	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
DÆK	Giant Gavia Fondo 0, tubeless, 700x32, folding
EKSTRA	Fender adapter
TILBEHØR	
LYGTER	Seatpost clamp integrated tail light

Pris: 51.609,00 kr.

GEOMETRI

RAMME	XS	S	M	L
Sadelrørslængde (mm)	400	435	470	505
Sadelrørsvinkel	74,5°	74,5°	74,0°	73,5°
Overrørslængde (mm)	515	525	540	555
Kronrørslængde (mm)	120	135	155	175
Kronrørsvinkel	70,5°	71,0°	72,0°	72,0°
Forgaffel fremspring (rake) (mm)	50	50	50	50
Akselafstand (mm)	993	999	1003	1013
Kædestagslængde (mm)	420	420	420	420
Krankboks drop (mm)	80	80	80	75
Stack (mm)	529	545	563	582
Reach (mm)	368	374	378	382
Skridthøjde (mm)	677	708	743	782
Styrbredde (mm)	380	400	400	420
Frempindslængde (mm)	80	90	100	110
Hjulstørrelse	700C	700C	700C	700C

Alle de anførte specifikationer kan ændres uden varsel.