

# AVAIL ADVANCED E+ ELITE 2



## SPECS

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Move Plus, Rear Hub, 30Nm
<b>CONTROLLER</b>	Mode support switch from SRAM blips
<b>DISPLAY</b>	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
<b>BATTERY</b>	EnergyPak Smart 400Wh EnergyPak Plus, range extender compatible
<b>CHARGER</b>	EnergyPak 4A smart charger compact
<b>MAXIMUM ASSISTED SPEED</b>	Pedal-assist limited to 25 km/h in accordance with Australian regulations (EN15194); no motor support above this speed
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Golden Haze
<b>FRAME</b>	Advanced-Grade Composite, disc, 12x145mm
<b>FORK</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, disc, 12x100mm
<b>SHOCK</b>	-
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact SL D-Fuse XS:38/40cm S:40/42cm, M:40/42cm, L:42/44cm
<b>GRIPS</b>	Stratus Lite 3.0
<b>STEM</b>	Giant Contact SL AeroLight XS: 80mm, S:90mm, M:100mm, L:110mm
<b>SEATPOST</b>	Giant D-Fuse, composite, -5/+15mm offset
<b>SADDLE</b>	Liv Approach
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM Rival AXS
<b>FRONT DERAILLEUR</b>	SRAM Rival AXS
<b>REAR DERAILLEUR</b>	SRAM Rival AXS
<b>BRAKES</b>	SRAM Rival AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Rival AXS hydraulic
<b>CASSETTE</b>	SRAM Rival XG-1250, 12-speed, 10-36
<b>CHAIN</b>	SRAM Rival D1
<b>CRANKSET</b>	SRAM Force X-SYNC 33/46T BCD107 chain ring Praxis E Crank Alloy ISIS, XS:165mm, S:165mm, M:170mm, L:172.5mm
<b>BOTTOM BRACKET</b>	Giant E+ System BBSS

WHEELS	
<b>RIMS</b>	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready
<b>HUBS</b>	[F] Giant Alloy, 24H [R] Giant SyncDrive Move Plus, 28H
<b>SPOKES</b>	Sapim spoke E-Light [R] Race [F], e-bike optimised
<b>TYRES</b>	Giant Gavia Fondo 0, tubeless, 700x32c, folding
<b>EXTRAS</b>	N/A
ACCESSORIES	
<b>LIGHTING</b>	Seatpost clamp integrated tail light

**Price: \$10,999.00**

## GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	400	435	470	505
Seat Tube Angle	74.5°	74.5°	74.0°	73.5°
Top Tube Length (mm)	515	525	540	555
Head Tube Length (mm)	120	135	155	175
Head Tube Angle	70.5°	71.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	72	68.3	61.8	61.8
Wheelbase (mm)	993	999.2	1003	1013.2
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	80	75
Stack (mm)	528.9	545	562.8	582.4
Reach (mm)	368	373.6	378.4	382.4
Stand Over Height (mm)	677	708	743	782.4
Stem Length (mm)	80	90	100	110
Crank Length (mm)	165	165	170	172.5
Wheel Size	700C	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.