AVAIL ADVANCED E+ ELITE 2



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
SENSOR	Mode support switch from SRAM Blips
ECRÃ	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATERIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARREGADOR	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
QUADRO	
TAMANHOS	XS, S, M, L
CORES	Iron Rouge/ Carbon Smoke
QUADRO	Advanced-grade composite,12x145 thru-axle
FORQUILHA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMORTECEDORES	-
COMPONENTES	
GUIADOR	Liv Contact SL D-Fuse 31.8 alloy
AVANÇO	Contact SL Aerolight 31.8 alloy
ESPIGÃO DE SELIM	Giant D-Fuse, Composite, 14mm offset
SELIM	Liv Approach
TRANSMISSÃO	
MANETES	Sram Rival AXS
DESVIADOR DIANTEIRO	Sram Rival AXS
DESVIADOR TRASEIRO	Sram Rival AXS
TRAVÕES	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
MANÍPULOS DOS TRAVÕES	Sram Rival AXS HRD
CASSETE	Sram Rival XG-1250 10x36T 12-speed
CORRENTE	Sram Rival 12-speed
CONJUNTO PEDALEIRO	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS"
MOVIMENTO CENTRAL	Giant E+ System BBSS

RODAS	
AROS	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
PNEUS	Giant Gavia Fondo 0, tubeless, 700x32, folding
EXTRAS	Fender adapter
ACESSÓRIOS	
LUZES	Seatpost clamp integrated tail light

Preço: 5 699,00 €

GEOMETRIA

QUADRO	XS	S	M	L
Comprimento do tubo do assento (mm)	400	435	470	505
Ângulo do tubo do assento	74,5°	74,5°	74,0°	73,5°
Comprimento do tubo superior (mm)	515	525	540	555
Comprimento do tubo principal (mm)	120	135	155	175
Ângulo do tubo principal	70,5°	71,0°	72,0°	72,0°
Garfo ancinho (mm)	50	50	50	50
distância entre eixos (mm)	993	999	1003	1013
Comprimento Chain Stay (mm)	420	420	420	420
Suporte inferior (mm)	80	80	80	75
Pilha (mm)	529	545	563	582
Alcançar (mm)	368	374	378	382
Altura do standover (mm)	677	708	743	782
Largura do guidão (mm)	380	400	400	420
Comprimento da haste (mm)	80	90	100	110
Tamanho da roda	700C	700C	700C	700C

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.