AVAIL ADVANCED E+ ELITE 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
SENSOR	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRU	
MARIMI	XS, S, M, L
CULORI	Iron Rouge/ Carbon Smoke
CADRU	Advanced-grade composite,12x145 thru-axle
FURCA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SOC	-
COMPONENTE	
GHIDON	Liv Contact SL D-Fuse 31.8 alloy
PIPA	Contact SL Aerolight 31.8 alloy
TIJA SA	Giant D-Fuse, Composite, 14mm offset
SA	Liv Approach
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Sram Rival AXS
SCHIMBATOR FATA	Sram Rival AXS
SCHIMBATOR SPATE	Sram Rival AXS
FRANE	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
MANETE FRANA	Sram Rival AXS HRD
PINIOANE	Sram Rival XG-1250 10x36T 12-speed
LANT	Sram Rival 12-speed
ANGRENAJ	Sram Force X-SYNC 33/46T BCD107 chain ring Praxis E crank Alloy ISIS"
BOTTOM BRACKET	Giant E+ System BBSS

ROTI	
JANTE	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
ANVELOPE	Giant Gavia Fondo 0, tubeless, 700x32, folding
EXTRAS	Fender adapter
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light

GEOMETRIE

CADRU	XS	S	M	L
Seat Tube Length (mm)	400	435	470	505
Seat Tube Angle	74,5°	74,5°	74,0°	73,5°
Top Tube Length (mm)	515	525	540	555
Head Tube Length (mm)	120	135	155	175
Head Tube Angle	70,5°	71,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50
Wheelbase (mm)	993	999	1003	1013
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	80	75
Stack (mm)	529	545	563	582
Reach (mm)	368	374	378	382
Stand Over Height (mm)	677	708	743	782
Handlebar Width (mm)	380	400	400	420
Stem Length (mm)	80	90	100	110
Wheel Size	700C	700C	700C	700C

Toate specificatiile enumerate se pot schimba fara notificare prealabila.