

# AVAIL ADVANCED E+ ELITE AR



## SPECS

HYBRID CYCLING TECHNOLOGY (PEDAL ASSIST)	
<b>MOTOR</b>	SyncDriveMove Plus Hub drive 75Nm max
<b>CONTROLLER</b>	Mode support switch from SRAM Blips
<b>DISPLAY</b>	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
<b>BATTERY</b>	EnergyPak Smart 400Wh by Panasonic, Aluminium casing with highest safety standard (UL2271, EN50604), CO2 Neutral production, 2300 charging cycles. EnergyPak Plus 200 range extender compatible
<b>CHARGER</b>	Giant EnergyPak 4A smart charger, 60% in 1:45
<b>CONNECTIVITY</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLOURS</b>	Gloss Silver Pine
<b>FRAME</b>	Advanced-grade composite, 12x145 thru-axle
<b>FORK</b>	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
<b>SHOCK</b>	-
COMPONENTS	
<b>HANDLEBAR</b>	Liv Contact SL D-Fuse 31.8 alloy
<b>STEM</b>	Contact SL Aerolight 31.8 alloy
<b>SEATPOST</b>	Giant D-Fuse, Composite, 14mm offset
<b>SADDLE</b>	Liv Approach
<b>PEDALS</b>	PEDALS NOT SUPPLIED
DRIVETRAIN	
<b>SHIFTERS</b>	Sram Rival eTap AXS 1x12
<b>FRONT DERAILLEUR</b>	-
<b>REAR DERAILLEUR</b>	Sram Rival XPLR eTap AXS
<b>BRAKES</b>	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
<b>BRAKE LEVERS</b>	Sram Rival eTap AXS HRD
<b>CASSETTE</b>	Sram Apex XPLR XG-1251, 10x44, 12-speed
<b>CHAIN</b>	Sram Rival 12-speed
<b>CRANKSET</b>	Sram X-SYNC 46T BCD107 chain ring Praxis E crank Alloy ISIS
<b>BOTTOM BRACKET</b>	Giant E+ System BBSS

WHEELS	
<b>RIMS</b>	Giant P-X2 Alloy Disc Wheel System, Tubeless Ready, 19mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimised
<b>SPOKES</b>	Sapim spoke E-Light [R] Race [F], e-bike optimised
<b>TYRES</b>	SCHWALBE G-ONE ALLROUND Perf, RaceGuard, Brown side-wall 700x35C 67EPI Tubeless
ACCESSORIES	
<b>LIGHTING</b>	Seatpost clamp integrated tail light

**Price: £5,999.00**

## GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	400	435	470	505
Seat Tube Angle	74.5°	74.5°	74.0°	73.5°
Top Tube Length (mm)	515	525	540	555
Head Tube Length (mm)	120	135	155	175
Head Tube Angle	70.5°	71.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	72	68.3	61.8	61.8
Wheelbase (mm)	993	999.2	1003	1013.2
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	80	75
Stack (mm)	528.9	545	562.8	582.4
Reach (mm)	368	373.6	378.4	382.4
Stand Over Height (mm)	677	708	743	782.4
Handlebar Width (mm)	380	400	400	420
Stem Length (mm)	80	90	100	110
Crank Length (mm)	165	165	170	172.5
Wheel Size	700C	700C	700C	700C

*Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.*