

AVAIL ADVANCED E+ ELITE AR



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDriveMove Plus Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	EnergyPak Smart 400Wh by Panasonic, Aluminium casing with highest safety standard (UL2271, EN50604), CO2 Neutral production, 2300 charging cycles. EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	XS, S, M, L
COLOURS	Gloss Silver Pine
FRAME	Advanced-grade composite, 12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SHOCK	-
COMPONENTS	
HANDLEBAR	Liv Contact SL D-Fuse 31.8 alloy
STEM	Contact SL Aerolight 31.8 alloy
SEATPOST	Giant D-Fuse, Composite, 14mm offset
SADDLE	Liv Approach
PEDALS	-
DRIVETRAIN	
SHIFTERS	Sram Rival eTap AXS 1x12
FRONT DERAILLEUR	-
REAR DERAILLEUR	Sram Rival XPLR eTap AXS
BRAKES	Sram Rival eTap HRD, Paceline 160mm center-lock [F] 160mm 6-bols [R]
BRAKE LEVERS	Sram Rival eTap AXS HRD
CASSETTE	Sram Apex XPLR XG-1251, 10x44, 12-speed
CHAIN	Sram Rival 12-speed
CRANKSET	Sram X-SYNC 46T BCD107 chain ring Praxis E crank Alloy ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS	
RIMS	Giant P-X2 Alloy Disc Wheel System, Tubeless Ready, 19mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimised
SPOKES	Sapim spoke E-Light [R] Race [F], e-bike optimised
TYRES	SCHWALBE G-ONE ALLROUND Perf, RaceGuard, Brown side-wall 700x35C 67EPI Tubeless
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	400	435	470	505
Seat Tube Angle	74.5°	74.5°	74.0°	73.5°
Top Tube Length (mm)	515	525	540	555
Head Tube Length (mm)	120	135	155	175
Head Tube Angle	70.5°	71.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50
Trail (mm)	72	68.3	61.8	61.8
Wheelbase (mm)	993	999.2	1003	1013.2
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	80	75
Stack (mm)	528.9	545	562.8	582.4
Reach (mm)	368	373.6	378.4	382.4
Stand Over Height (mm)	677	708	743	782.4
Handlebar Width (mm)	380	400	400	420
Stem Length (mm)	80	90	100	110
Crank Length (mm)	165	165	170	172.5
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.