

AVAIL ADVANCED E+ ELITE AR



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
CONTROLLER	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	XS, S, M, L
COLOURS	Eucalyptus/ Ocean Storm
FRAME	Advanced-grade composite, 12x145 thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
SHOCK	-
COMPONENTS	
HANDLEBAR	Liv Contact SL D-Fuse 31.8 alloy
STEM	Contact SL Aerolight 31.8 alloy
SEATPOST	Giant D-Fuse, Composite, 14mm offset
SADDLE	Liv Approach
DRIVETRAIN	
SHIFTERS	Sram Rival AXS
FRONT DERAILLEUR	n/a
REAR DERAILLEUR	Sram Rival XPLR AXS
BRAKES	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
BRAKE LEVERS	Sram Rival AXS HRD
CASSETTE	Sram XPLR XG-1251 10x44T 12-speed
CHAIN	Sram Rival 12-speed
CRANKSET	Sram X-SYNC 46T BCD107 chain ring Praxis E crank Alloy ISIS
BOTTOM BRACKET	Giant E+ System BBSS

WHEELS	
RIMS	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
TYRES	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
EXTRAS	Fender adapter
ACCESSORIES	
LIGHTING	Seatpost clamp integrated tail light

Price: €6,599.00

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	400	435	470	505
Seat Tube Angle	74.5°	74.5°	74.0°	73.5°
Top Tube Length (mm)	515	525	540	555
Head Tube Length (mm)	120	135	155	175
Head Tube Angle	70.5°	71.0°	72.0°	72.0°
Fork Rake (mm)	50	50	50	50
Wheelbase (mm)	993	999	1003	1013
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	80	75
Stack (mm)	529	545	563	582
Reach (mm)	368	374	378	382
Stand Over Height (mm)	677	708	743	782
Handlebar Width (mm)	380	400	400	420
Stem Length (mm)	80	90	100	110
Wheel Size	700C	700C	700C	700C

All specifications listed are subject to change without notice.