AVAIL ADVANCED E+ ELITE AR



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	SyncDrive Move Plus, Hub drive 75Nm max
COMANDO	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CARICATORE	Giant EnergyPak smart charger 4A
CONNETTIVITÀ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
TELAIO	
TAGLIE	XS, S, M, L
COLORAZIONI	Eucalyptus/ Ocean Storm
TELAIO	Advanced-grade composite,12x145 thru-axle
FORCELLA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
AMMORTIZZATORE	-
COMPONENTISTICA	
MANUBRIO	Liv Contact SL D-Fuse 31.8 alloy
ATTACCO MANUBRIO	Contact SL Aerolight 31.8 alloy
REGGISELLA	Giant D-Fuse, Composite, 14mm offset
SELLA	Liv Approach
SISTEMA DI TRASMISSIONE	
CAMBIO	Sram Rival AXS
DERAGLIATORE ANTERIORE	n/a
DERAGLIATORE POSTERIORE	Sram Rival XPLR AXS
FRENI	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
COMANDI FRENO	Sram Rival AXS HRD
PACCO PIGNONI	Sram XPLR XG-1251 10x44T 12-speed
CATENA	Sram Rival 12-speed
GUARNITURA	Sram X-SYNC 46T BCD107 chain ring Praxis E crank Alloy ISIS
MOVIMENTO CENTRALE	Giant E+ System BBSS

RUOTE	
CERCHI	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
COPERTONI	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
EXTRA	Fender adapter
ACCESSORI	
ILLUMINAZIONE	Seatpost clamp integrated tail light

Prezzo: 5.899,00 €

GEOMETRIA

TELAIO	XS	S	M	L
Lunghezza Tubo Sella (mm)	400	435	470	505
Angolo Tubo Sella	74,5°	74,5°	74,0°	73,5°
Lunghezza Tubo Orizzontale (mm)	515	525	540	555
Lunghezza Tubo Sterzo (mm)	120	135	155	175
Angolo Sterzo	70,5°	71,0°	72,0°	72,0°
Rake Forcella (mm)	50	50	50	50
Interasse (mm)	993	999	1003	1013
Lunghezza Carro Posteriore (mm)	420	420	420	420
Drop Movimento Centrale (mm)	80	80	80	75
Stack (mm)	529	545	563	582
Reach (mm)	368	374	378	382
Altezza stand over (mm)	677	708	743	782
Larghezza Manubrio c/c (mm)	380	400	400	420
Lunghezza Attacco Manubrio (mm)	80	90	100	110
Dimensione Ruote	700C	700C	700C	700C

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.