AVAIL ADVANCED E+ ELITE AR



SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
SENSOR	Mode support switch from SRAM Blips
DISPLAY	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATTERI	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak smart charger 4A
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAMME	
STØRRELSE	XS, S, M, L
FARGE	Eucalyptus/ Ocean Storm
RAMME	Advanced-grade composite,12x145 thru-axle
GAFFEL	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
DEMPER	-
KOMPONENTER	
STYRE	Liv Contact SL D-Fuse 31.8 alloy
STYRSTEM	Contact SL Aerolight 31.8 alloy
SETEPINNE	Giant D-Fuse, Composite, 14mm offset
SADEL	Liv Approach
DRIVVERK	
GIRHENDLER	Sram Rival AXS
FRONTGIR	n/a
BAKGIR	Sram Rival XPLR AXS
BREMSER	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
BREMSEHENDLER	Sram Rival AXS HRD
KASSETT	Sram XPLR XG-1251 10x44T 12-speed
KJEDE	Sram Rival 12-speed
KRANK	Sram X-SYNC 46T BCD107 chain ring Praxis E crank Alloy ISIS
BOTTOM BRACKET	Giant E+ System BBSS

HJUL	
FELG	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
DEKK	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
EXTRAS	Fender adapter
TILBEHØR	
LYS	Seatpost clamp integrated tail light

GEOMETRI

RAMME	XS	S	M	L
Seat Tube Length (mm)	400	435	470	505
Seat Tube Angle	74,5°	74,5°	74,0°	73,5°
Top Tube Length (mm)	515	525	540	555
Head Tube Length (mm)	120	135	155	175
Head Tube Angle	70,5°	71,0°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50
Wheelbase (mm)	993	999	1003	1013
Chain Stay Length (mm)	420	420	420	420
Bottom Bracket Drop (mm)	80	80	80	75
Stack (mm)	529	545	563	582
Reach (mm)	368	374	378	382
Stand Over Height (mm)	677	708	743	782
Handlebar Width (mm)	380	400	400	420
Stem Length (mm)	80	90	100	110
Wheel Size	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.