AVAIL ADVANCED E+ ELITE AR



ŠPECIFIKÁCIE

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Move Plus, Hub drive 75Nm max
OVLÁDAČ	Mode support switch from SRAM Blips
OVLÁDACIA JEDNOTKA	Giant RideControl GO, frame-integrated LED console Optional wireless ANT+ display
BATÉRIA	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
NABÍJAČKA	Giant EnergyPak smart charger 4A
KONEKTIVITA	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RÁM	
VEĽKOSTI	XS, S, M, L
FARBY	Eucalyptus/ Ocean Storm
RÁM	Advanced-grade composite,12x145 thru-axle
VIDLICA	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
TLMIČ	-
KOMPONENTY	
RIADIDLÁ	Liv Contact SL D-Fuse 31.8 alloy
PREDSTAVEC	Contact SL Aerolight 31.8 alloy
SEDLOVKA	Giant D-Fuse, Composite, 14mm offset
SEDADLO	Liv Approach
POHON	
RADENIE	Sram Rival AXS
PREŠMYKAČ	n/a
PREHADZOVAČKA	Sram Rival XPLR AXS
BRZDY	Sram Rival AXS HRD, Paceline 160mm 6-bols [F/R]
BRZDOVÉ PÁKY	Sram Rival AXS HRD
KAZETA	Sram XPLR XG-1251 10x44T 12-speed
REŤAZ	Sram Rival 12-speed
KĽUKY	Sram X-SYNC 46T BCD107 chain ring Praxis E crank Alloy ISIS
STREDOVÉ ZLOŽENIE	Giant E+ System BBSS

KOLESÁ	
RÁFIKY	Giant P-R2 Alloy Disc Wheel System, Tubeless Ready, 22mm inner width, 12mm thru-axle, w/ Sapim spoke E-Light [R] Race [F], e-bike optimized
PNEUMATIKY	Schwalbe G-one Allround Performance, RaceGuard, Brown side-wall, tubeless, 700x35
DOPLNKY	Fender adapter
PRÍSLUŠENSTVO	
OSVETLENIE	Seatpost clamp integrated tail light

Cena: 6 599 €

GEOMETRIA

RÁM	XS	S	M	L
Dĺžka sedlovej trubky (mm)	400	435	470	505
Uhol sedlovej trubky	74,5°	74,5°	74,0°	73,5°
Dĺžka hornej rámovej trubky (mm)	515	525	540	555
Dĺžka hlavovej trubky (mm)	120	135	155	175
Uhol hlavovej trubky	70,5°	71,0°	72,0°	72,0°
Offset vidlice (mm)	50	50	50	50
Rázvor (mm)	993	999	1003	1013
Dĺžka zadnej stavby (mm)	420	420	420	420
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	80	80	80	75
Stack - výška riadenia (mm)	529	545	563	582
Reach (mm)	368	374	378	382
Výška rámu od zeme (mm)	677	708	743	782
Šírka riaditok (mm)	380	400	400	420
Dĺžka predstavca (mm)	80	90	100	110
Rozmer kolies	700C	700C	700C	700C

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.