

AVAIL ADVANCED PRO 0



SPECS

| FRAME | |
|-------------------------|---|
| SIZES | XS, S, M, L |
| COLOURS | Gloss Carbon/Matte Carbon/Chrome |
| FRAME | Advanced-grade composite, 12x142mm thru-axle, disc |
| FORK | Advanced SL-grade composite, full-composite OverDrive Aero steerer, 12x100mm, disc |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Giant Contact SLR D-Fuse, 31.8mm XS:38cm, S:40cm, M:40cm, L:42cm |
| GRIPS | Liv All Condition |
| STEM | Giant Contact SL Aerolight XS:70mm, S:80mm, M:90mm, L:90mm |
| SEATPOST | Giant D-Fuse SLR, composite, -5/+15mm offset |
| SADDLE | Liv Alacra SL |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | Shimano Ultegra Di2 ST-R8170 |
| FRONT DERAILLEUR | Shimano Ultegra Di2 FD-R8150 |
| REAR DERAILLEUR | Shimano Ultegra Di2 RD-R8150 |
| BRAKES | Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm |
| BRAKE LEVERS | Shimano Ultegra Di2 hydraulic |
| CASSETTE | Shimano Ultegra, 12-speed, 11x34 |
| CHAIN | KMC X12 |
| CRANKSET | Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:165mm, S:170mm, M:170mm, L:172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|---------------|---|
| RIMS | Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm |
| HUBS | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle |
| SPOKES | Sapim CX-Ray |
| TIRES | Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding |
| EXTRAS | Computer mount, water bottle cages, tubeless prepared, 38mm max tyre size |

Price: \$7,999.00

GEOMETRY

| FRAME | XS | S | M | L |
|--------------------------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 405 | 435 | 465 | 495 |
| Seat Tube Angle | 74.5° | 74.5° | 74.0° | 74.0° |
| Top Tube Length (mm) | 520 | 525 | 535 | 555 |
| Head Tube Length (mm) | 125 | 145 | 165 | 185 |
| Head Tube Angle | 71.0° | 71.0° | 71.0° | 72.0° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 |
| Trail (mm) | 68 | 68 | 68 | 61 |
| Wheelbase (mm) | 995 | 1002 | 1007 | 1013 |
| Chain Stay Length (mm) | 420 | 420 | 420 | 420 |
| Bottom Bracket Drop (mm) | 75 | 73 | 73 | 73 |
| Stack (mm) | 528 | 547 | 566 | 589 |
| Reach (mm) | 373 | 373 | 373 | 381 |
| Stand Over Height (mm) | 712 | 737 | 762 | 789 |
| Stem Length (mm) | 70 | 80 | 90 | 90 |
| Crank Length (mm) | 165 | 170 | 170 | 172.5 |
| Wheel Size | 700C | 700C | 700C | 700C |

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.