

# AVAIL ADVANCED PRO 0



## SPECS

| FRAME                   |   |
|-------------------------|---|
| <b>SIZES</b>            | XXS, XS, S, M, L  |
| <b>COLOURS</b>          | Dreamy Blue/Carbon/Chrome   |
| <b>FRAME</b>            | Advanced-grade composite, 12x142mm thru-axle, disc  |
| <b>FORK</b>             | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc      |
| <b>SHOCK</b>            | N/A   |
| COMPONENTS              |   |
| <b>HANDLEBAR</b>        | Liv Contact SLR D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm               |
| <b>GRIPS</b>            | Liv Stratus Elite 2.0   |
| <b>STEM</b>             | Giant Contact SL AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm                        |
| <b>SEATPOST</b>         | Giant D-Fuse SLR, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm |
| <b>SADDLE</b>           | Liv Alacra SL   |
| <b>PEDALS</b>           | PEDALS NOT SUPPLIED   |
| DRIVETRAIN              |   |
| <b>SHIFTERS</b>         | Shimano Ultegra Di2 ST-R8170  |
| <b>FRONT DERAILLEUR</b> | Shimano Ultegra Di2 FD-R8150  |
| <b>REAR DERAILLEUR</b>  | Shimano Ultegra Di2 RD-R8150  |
| <b>BRAKES</b>           | Shimano Ultegra hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]160mm                            |
| <b>BRAKE LEVERS</b>     | Shimano Ultegra hydraulic   |
| <b>CASSETTE</b>         | Shimano Ultegra, 12-speed, 11x34  |
| <b>CHAIN</b>            | Shimano CN-M8100  |
| <b>CRANKSET</b>         | Shimano Ultegra, 34/50 with Giant power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm   |
| <b>BOTTOM BRACKET</b>   | Shimano, press fit  |

| WHEELS                    |  |
|---------------------------|--|
| <b>RIMS</b>               | Giant SLR 0 40 WheelSystem, [F] 36mm, [R] 36mm   |
| <b>HUBS</b>               | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle |
| <b>SPOKES</b>             | Sapim CX-Ray   |
| <b>TYRES</b>              | CADEX Classic 32, tubeless, 700x32c, folding   |
| <b>EXTRAS</b>             | two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size   |
| LIMITS                    |  |
| <b>MAX TYRE CLEARANCE</b> | 40mm   |

**Price: £5,499.00**

## GEOMETRY

| FRAME                    | XXS   | XS    | S     | M     | L     |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm)    | 385   | 405   | 435   | 465   | 495   |
| Seat Tube Angle          | 75.0° | 74.5° | 74.5° | 74.0° | 74.0° |
| Top Tube Length (mm)     | 500   | 520   | 525   | 535   | 550   |
| Head Tube Length (mm)    | 110   | 125   | 145   | 165   | 185   |
| Head Tube Angle          | 69.8° | 71.0° | 71.0° | 71.0° | 72.0° |
| Fork Rake (mm)           | 50    | 50    | 50    | 50    | 50    |
| Trail (mm)               | 76.2  | 68.3  | 68.3  | 68.3  | 61.8  |
| Wheelbase (mm)           | 989   | 995   | 1002  | 1007  | 1013  |
| Chain Stay Length (mm)   | 420   | 420   | 420   | 420   | 420   |
| Bottom Bracket Drop (mm) | 75    | 75    | 75    | 75    | 75    |
| Stack (mm)               | 510   | 528   | 547   | 566   | 589   |
| Reach (mm)               | 363   | 373   | 373   | 373   | 381   |
| Stand Over Height (mm)   | 683   | 712   | 737   | 762   | 789   |
| Handlebar Width (mm)     | 380   | 380   | 400   | 400   | 420   |
| Stem Length (mm)         | 70    | 70    | 80    | 90    | 90    |
| Crank Length (mm)        | 160   | 165   | 165   | 170   | 172.5 |

*Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.*