

AVAIL ADVANCED PRO 0



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XXS, XS, S, M, L
COLORIS	Dreamy Blue/Carbon/Chrome
CADRE	Advanced-grade composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTISSEUR	N/A
COMPOSANTS	
CINTRE	Liv Contact SLR D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
POIGNÉES	Liv Stratus Elite 2.0
POTENCE	Giant Contact SL AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
TIGE DE SELLE	Giant D-Fuse SLR, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SELLE	Liv Alacra SL
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Ultegra Di2 ST-R8170
DÉRAILLEUR AVANT	Shimano Ultegra Di2 FD-R8150
DÉRAILLEUR ARRIÈRE	Shimano Ultegra Di2 RD-R8150
FREINS	Shimano Ultegra hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]160mm
LEVIERS DE FREIN	Shimano Ultegra hydraulic
CASSETTE	Shimano Ultegra, 12-speed, 11x34
CHAÎNE	Shimano CN-M8100
PÉDALIER	Shimano Ultegra, 34/50 with Giant power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant SLR 0 40 WheelSystem, [F] 36mm, [R] 36mm
MOYEURS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Sapim CX-Ray
PNEUS	CADEX Classic 32, tubeless, 700x32c, folding
EXTRAS	two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GÉOMÉTRIE

CADRE	XXS	XS	S	M	L
Longueur de tube de selle (mm)	385	405	435	465	495
Angle de tube de selle	75,0°	74,5°	74,5°	74,0°	74,0°
Longueur du tube supérieur (mm)	500	520	525	535	550
Longueur du tube de direction (mm)	110	125	145	165	185
Angle du tube de direction	69,8°	71,0°	71,0°	71,0°	72,0°
Déport de fourche (mm)	50	50	50	50	50
Chasse (mm)	76,2	68,3	68,3	68,3	61,8
Empattement (mm)	989	995	1002	1007	1013
Longueur des bases (mm)	420	420	420	420	420
Hauteur du boîtier de pédalier (mm)	75	75	75	75	75
Stack (mm)	510	528	547	566	589
Reach (mm)	363	373	373	373	381
Hauteur d'enjambement (mm)	683	712	737	762	789
Largeur de cintre (mm)	380	380	400	400	420
Longueur de potence (mm)	70	70	80	90	90
Longueur des manivelles (mm)	160	165	165	170	172,5

Giant Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.