

# AVAIL ADVANCED PRO 0



## SPECIFIKACIJE

OKVIR	
VELIČINE	XXS, XS, S, M, L
BOJE	Dreamy Blue/Carbon/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc
VILICA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
AMORTIZER	N/A
KOMPONENTE	
VOLAN	Liv Contact SLR D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
LULA VOLANA	Giant Contact SL AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
CIJEV SJEDALA	Giant D-Fuse SLR, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SJEDALO	Liv Alacra SL
POGON	
RUČICE MJENJAČA	Shimano Ultegra Di2 ST-R8170
PREDNJI MJENJAČ	Shimano Ultegra Di2 FD-R8150
STRAŽNJI MJENJAČ	Shimano Ultegra Di2 RD-R8150
KOČNICE	Shimano Ultegra hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]160mm
RUČICE KOČNICA	Shimano Ultegra hydraulic
KAZETA	Shimano Ultegra, 12-speed, 11x34
LANAC	Shimano CN-M8100
POGON	Shimano Ultegra, 34/50 with Giant power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
OSOVINA POGONA (BB)	Shimano, press fit

KOTAČI	
OBRUČI	Giant SLR 0 40 WheelSystem, [F] 36mm, [R] 36mm
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	Sapim CX-Ray
GUME	CADEX Classic 32, tubeless, 700x32c, folding
DODACI	two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

## GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dužina cijevi sjedala (mm)	385	405	435	465	495
Kut cijevi sjedala	75,0°	74,5°	74,5°	74,0°	74,0°
Dužina gornje cijevi (mm)	500	520	525	535	550
Dužina prednje cijevi (mm)	110	125	145	165	185
Kut vilice	69,8°	71,0°	71,0°	71,0°	72,0°
Zakrivljenost vilice (offset) (mm)	50	50	50	50	50
Staza (mm)	76,2	68,3	68,3	68,3	61,8
Međusovinski razmak kotača (mm)	989	995	1002	1007	1013
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	420	420	420	420	420
Položaj osovine pogona (mm)	75	75	75	75	75
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	510	528	547	566	589
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	363	373	373	373	381
Prekoračna visina (mm)	683	712	737	762	789
Širina volana (mm)	380	380	400	400	420
Dužina lule volana (mm)	70	70	80	90	90
Dužina poluge pedale (mm)	160	165	165	170	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.