AVAIL ADVANCED PRO 0



SPECS

RAMME	
STØRRELSE	XXS, XS, S, M, L
FARGE	Gloss Carbon/Matte Carbon/Chrome
RAMME	Advanced-grade composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-grade composite, full-composite OverDrive Aero steerer, stainless steel bearings 12x100mm, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Liv Contact SLR D-Fuse, 31.8mm, 8-degree flare drop XXS: 410/380mm, XS: 410/380mm, S: 430/400mm, M: 430/400mm, L: 450/420mm
GRIPS	Liv All Condition
STYRSTEM	Giant Contact SL AeroLight XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SETEPINNE	Giant D-Fuse SLR, composite, -5/+15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADEL	Liv Alacra SL
PEDALER	N/A
DRIVVERK	
GIRHENDLER	Shimano Ultegra Di2 ST-R8170
FRONTGIR	Shimano Ultegra Di2 FD-R8150
BAKGIR	Shimano Ultegra Di2 RD-R8150
BREMSER	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
BREMSEHENDLER	Shimano Ultegra Di2 hydraulic
KASSETT	Shimano Ultegra, 12-speed, 11x34
KJEDE	KMC X12
KRANK	Shimano Ultegra, 34/50 with Giant PowerPro power meter XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
BOTTOM BRACKET	Shimano, press fit

HJUL	
FELG	Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
EIKE	Sapim
DEKK	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
EXTRAS	tubeless prepared, two bottle cages, 38mm max tire size, fender mount, computer mount

GEOMETRI

RAMME	XXS	XS	S	M	L
Seat Tube Length (mm)	385	405	435	465	495
Seat Tube Angle	75,0°	74,5°	74,5°	74,0°	74,0°
Top Tube Length (mm)	500	520	525	535	555
Head Tube Length (mm)	110	125	145	165	185
Head Tube Angle	69,8°	71,0°	71,0°	71,0°	72,0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	76	68	68	68	61
Wheelbase (mm)	989	995	1002	1007	1013
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	73	73	73
Stack (mm)	510	528	547	566	589
Reach (mm)	363	373	373	373	381
Stand Over Height (mm)	683	712	737	762	789
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	165	165	170	170	172,5
Wheel Size	700C	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.