

AVAIL ADVANCED PRO 0



SPECS

| FRAME | |
|-------------------------|---|
| SIZES | XXS, XS, S, M, L |
| COLORS | Dreamy Blue/Carbon/Chrome |
| FRAME | Advanced-grade composite, 12x142mm thru-axle, disc |
| FORK | Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc |
| SHOCK | N/A |
| COMPONENTS | |
| HANDLEBAR | Liv Contact SLR D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm |
| GRIPS | Liv Stratus Elite 2.0 |
| STEM | Giant Contact SL AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm |
| SEATPOST | Giant D-Fuse SLR, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm |
| SADDLE | Liv Alacra SL |
| DRIVETRAIN | |
| SHIFTERS | Shimano Ultegra Di2 ST-R8170 |
| FRONT DERAILLEUR | Shimano Ultegra Di2 FD-R8150 |
| REAR DERAILLEUR | Shimano Ultegra Di2 RD-R8150 |
| BRAKES | Shimano Ultegra hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]160mm |
| BRAKE LEVERS | Shimano Ultegra hydraulic |
| CASSETTE | Shimano Ultegra, 12-speed, 11x34 |
| CHAIN | Shimano CN-M8100 |
| CRANKSET | Shimano Ultegra, 34/50 with Giant power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm |
| BOTTOM BRACKET | Shimano, press fit |

| WHEELS | |
|---------------------------|--|
| RIMS | Giant SLR 0 40 WheelSystem, [F] 36mm, [R] 36mm |
| HUBS | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle |
| SPOKES | Sapim CX-Ray |
| TIRES | CADEX Classic 32, tubeless, 700x32c, folding |
| EXTRAS | two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size |
| LIMITS | |
| MAX TIRE CLEARANCE | 40mm |

GEOMETRY

| FRAME | XXS | XS | S | M | L |
|--------------------------|-------|-------|-------|-------|-------|
| Seat Tube Length (mm) | 385 | 405 | 435 | 465 | 495 |
| Seat Tube Angle | 75,0° | 74,5° | 74,5° | 74,0° | 74,0° |
| Top Tube Length (mm) | 500 | 520 | 525 | 535 | 550 |
| Head Tube Length (mm) | 110 | 125 | 145 | 165 | 185 |
| Head Tube Angle | 69,8° | 71,0° | 71,0° | 71,0° | 72,0° |
| Fork Rake (mm) | 50 | 50 | 50 | 50 | 50 |
| Trail (mm) | 76,2 | 68,3 | 68,3 | 68,3 | 61,8 |
| Wheelbase (mm) | 989 | 995 | 1002 | 1007 | 1013 |
| Chain Stay Length (mm) | 420 | 420 | 420 | 420 | 420 |
| Bottom Bracket Drop (mm) | 75 | 75 | 75 | 75 | 75 |
| Stack (mm) | 510 | 528 | 547 | 566 | 589 |
| StackToHandlebar (mm) | 588 | 606 | 626 | 647 | 668 |
| Reach (mm) | 363 | 373 | 373 | 373 | 381 |
| ReachToHandlebar (mm) | 408 | 420 | 429 | 439 | 449 |
| Stand Over Height (mm) | 683 | 712 | 737 | 762 | 789 |
| Handlebar Width (mm) | 380 | 380 | 400 | 400 | 420 |
| Stem Length (mm) | 70 | 70 | 80 | 90 | 90 |
| Crank Length (mm) | 160 | 165 | 165 | 170 | 172,5 |

All specifications listed are subject to change without notice.