AVAIL ADVANCED PRO 0



ŠPECIFIKÁCIE

RÁM	
VEĽKOSTI	XXS, XS, S, M, L
FARBY	Gloss Carbon/Matte Carbon/Chrome
RÁM	Advanced-grade composite, 12x142mm thru-axle, disc
VIDLICA	Advanced SL-grade composite, full-composite OverDrive Aero steerer, stainless steel bearings 12x100mm, disc
TLMIČ	N/A
KOMPONENTY	
RIADIDLÁ	Liv Contact SLR D-Fuse, 31.8mm, 8-degree flare drop XXS: 410/380mm, XS: 410/380mm, S: 430/400mm, M: 430/400mm, L: 450/420mm
GRIPY	Liv All Condition
PREDSTAVEC	Giant Contact SL AeroLight XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SEDLOVKA	Giant D-Fuse SLR, composite, -5/+15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SEDADLO	Liv Alacra SL
PEDÁLE	N/A
POHON	
RADENIE	Shimano Ultegra Di2 ST-R8170
PREŠMYKAČ	Shimano Ultegra Di2 FD-R8150
PREHADZOVAČKA	Shimano Ultegra Di2 RD-R8150
BRZDY	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
BRZDOVÉ PÁKY	Shimano Ultegra Di2 hydraulic
KAZETA	Shimano Ultegra, 12-speed, 11x34
REŤAZ	KMC X12
KĽUKY	Shimano Ultegra, 34/50 with Giant PowerPro power meter XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
STREDOVÉ ZLOŽENIE	Shimano, press fit

KOLESÁ	
RÁFIKY	Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
NÁBOJE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
ŠPICE	Sapim
PNEUMATIKY	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
DOPLNKY	tubeless prepared, two bottle cages, 38mm max tire size, fender mount, computer mount

Cena: 6 399 €

GEOMETRIA

RÁM	XXS	XS	S	M	L
Dĺžka sedlovej trubky (mm)	385	405	435	465	495
Uhol sedlovej trubky	75,0°	74,5°	74,5°	74,0°	74,0°
Dĺžka hornej rámovej trubky (mm)	500	520	525	535	555
Dĺžka hlavovej trubky (mm)	110	125	145	165	185
Uhol hlavovej trubky	69,8°	71,0°	71,0°	71,0°	72,0°
Offset vidlice (mm)	50	50	50	50	50
Trail (mm)	76	68	68	68	61
Rázvor (mm)	989	995	1002	1007	1013
Dĺžka zadnej stavby (mm)	420	420	420	420	420
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	75	75	73	73	73
Stack - výška riadenia (mm)	510	528	547	566	589
Reach (mm)	363	373	373	373	381
Výška rámu od zeme (mm)	683	712	737	762	789
Šírka riaditok (mm)	380	380	400	400	420
Dĺžka predstavca (mm)	70	70	80	90	90
Dĺžka kľúk (mm)	165	165	170	170	172,5
Rozmer kolies	700C	700C	700C	700C	700C

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.