AVAIL ADVANCED PRO 0



產品規格

車架	
尺寸	XXS, XS, S
顏色	Gloss Carbon/Matte Carbon/Chrome碳纖黑
車架	Advanced-grade composite, 12x142mm thru-axle, disc
前叉	Advanced SL-grade composite, full-composite OverDrive 2 steerer, stainless steel bearings 12x100mm, disc
避震器	N/A
COMPONENTS	
車把手	Liv Contact SLR D-Fuse, 31.8mm, 8-degree flare drop XXS: 410/380mm, XS: 410/380mm, S: 430/400mm,
把手帶/套	Liv All Condition
豎桿	Giant Contact SL AeroLight XXS: 70mm, XS: 70mm, S: 80mm,
座桿	Giant D-Fuse SLR, composite, -5/+15mm offset XXS: 350mm, XS: 350mm, S: 350mm,
坐墊	Liv Alacra SL
踏板	N/A
DRIVETRAIN	
變速把手	Shimano Ultegra Di2 ST-R8170
前變速器	Shimano Ultegra Di2 FD-R8150
後變速器	Shimano Ultegra Di2 RD-R8150
煞車系統	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
煞車把手	Shimano Ultegra Di2 hydraulic
飛輪	Shimano Ultegra, 12-speed, 11x34
鏈條	KMC X12
大齒盤	Shimano Ultegra, 34/50 with Giant PowerPro power meter XXS:165mm, XS:165mm, S:170mm
BOTTOM BRACKET (B B)	Shimano, press fit

輪組	
輪圈	Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
花鼓	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
輻條	Sapim
外胎	Giant Gavia Fondo 0, tubeless, 700x32c (33.5mm), folding
其他	tubeless prepared, two bottle cages, 38mm max tire size, fender mount, computer mount

Price: NT$158,000

車架幾何

車架	XXS	XS	S
座(立)管長 (mm)	385	405	435
座(立)管角度	75.0°	74.5°	74.5°
上管長度 (mm)	500	520	525
頭管長度 (mm)	110	125	145
頭管角度	69.8°	71.0°	71.0°
前叉 (mm)	50	50	50
Trail (mm)	76	68	68
前後輪距 (mm)	989	995	1002
後下叉長度 (mm)	420	420	420
五通下降高度 (mm)	75	75	73
頭碗至五通高度 (mm)	510	528	547
頭碗至五通長度 (mm)	363	373	373
上管至地面高度 (mm)	683	712	737
把手寬 (mm)	380	380	400
龍頭長度 (mm)	70	70	80
曲柄長度 (mm)	165	165	170
輪組尺寸	700C	700C	700C

＊捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。