

# AVAIL ADVANCED PRO 0



## 產品規格

車架	
尺寸	XXS, XS, S, M, L
顏色	Dreamy Blue/Carbon/Chrome
車架	Advanced-grade composite, 12x142mm thru-axle, disc
前叉	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
避震器	N/A
COMPONENTS	
車把手	Liv Contact SLR D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
把手帶/套	Liv Stratus Elite 2.0
豎桿	Giant Contact SL Aerolight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
座桿	Giant D-Fuse SLR, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
坐墊	Liv Alacra SL
DRIVETRAIN	
變速把手	Shimano Ultegra Di2 ST-R8170
前變速器	Shimano Ultegra Di2 FD-R8150
後變速器	Shimano Ultegra Di2 RD-R8150
煞車系統	Shimano Ultegra hydraulic, Shimano RT-CL800 rotors, [F]160mm, [R]160mm
煞車把手	Shimano Ultegra hydraulic
飛輪	Shimano Ultegra, 12-speed, 11x34
鍊條	Shimano CN-M8100
大齒盤	Shimano Ultegra, 34/50 with Giant power meter, XXS:160mm, XS:165mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET (B B)	Shimano, press fit

輪組	
輪圈	Giant SLR 0 40 WheelSystem, [F] 36mm, [R] 36mm
花鼓	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
輻條	Sapim CX-Ray
外胎	CADEX Classic 32, tubeless, 700x32c, folding
其他	two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

Price: NT\$168,000

## 車架幾何

車架	XXS	XS	S
座(立)管長 (mm)	385	405	435
座(立)管角度	75.0°	74.5°	74.5°
上管長度 (mm)	500	520	525
頭管長度 (mm)	110	125	145
頭管角度	69.8°	71.0°	71.0°
前叉 (mm)	50	50	50
Trail (mm)	76.2	68.3	68.3
前後輪距 (mm)	989	995	1002
後下叉長度 (mm)	420	420	420
五通下降高度 (mm)	75	75	75
頭碗至五通高度 (mm)	510	528	547
StackToHandlebar (mm)	588	606	626
頭碗至五通長度 (mm)	363	373	373
ReachToHandlebar (mm)	408	420	429
上管至地面高度 (mm)	683	712	737
把手寬 (mm)	380	380	400
龍頭長度 (mm)	70	70	80
曲柄長度 (mm)	160	165	165

\*捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。