

AVAIL ADVANCED PRO 1



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Dreamy Blue/Carbon
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Liv Contact SL D-Fuse, 31.8mm XS:38/41cm, S:40/43cm, M:40/43cm
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SL Aerolight XS:70mm, S:80mm, M:90mm
SEATPOST	Giant D-Fuse SL, composite, 16mm offset
SADDLE	Liv Alacra SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Rival AXS E1
FRONT DERAILLEUR	SRAM Rival AXS E1
REAR DERAILLEUR	SRAM Rival AXS E1
BRAKES	SRAM Rival E1 hydraulic, SRAM PaceLine rotors, [F] 160mm, [R] 140mm
BRAKE LEVERS	SRAM Rival AXS E1
CASSETTE	SRAM Rival E1, 12-speed, 10x36
CHAIN	SRAM Rival E1
CRANKSET	SRAM Rival E1 DUB, 33/46 with spindle power meter XS:165mm, S:165mm, M:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 1 40 WheelSystem, [F] 40mm, [R] 40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	Giant Gavia Fondo 0, tubeless, 700x32c, folding
EXTRAS	Computer mount, water bottle cages, tubeless prepared, 38mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	38mm

Price: \$6,799.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	405	435	465
Seat Tube Angle	74.5°	74.5°	74.0°
Top Tube Length (mm)	520	525	535
Head Tube Length (mm)	125	145	165
Head Tube Angle	71.0°	71.0°	71.0°
Fork Rake (mm)	50	50	50
Trail (mm)	68.3	68.3	68.3
Wheelbase (mm)	995	1002	1007
Chain Stay Length (mm)	420	420	420
Bottom Bracket Drop (mm)	75	75	75
Stack (mm)	528	547	566
Reach (mm)	373	373	373
Stand Over Height (mm)	712	737	762
Stem Length (mm)	70	80	90
Crank Length (mm)	165	170	170

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.