

AVAIL ADVANCED PRO 1



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
FRAME	Advanced-Grade Composite, 12x142mm thru-axle
FORK	Advanced SL-Grade Composite, Full-Composite OverDrive Aero Steerer, 12x100mm thru-axle, Disc
COMPONENTS	
HANDLEBAR	Liv Contact SL D-Fuse, 31.8, Reach: 68mm, Drop: 120mm XXS: Down: 410 / Top: 380, XS: Down: 410 / Top: 380, S: Down: 430 / Top: 400, M: Down: 430 / Top: 400, L: Down: 450 / Top: 420
GRIPS	Liv Stratus Elite 2.0
STEM	Giant Contact SL Aerolight, -10° XXS: 70, XS: 70, S: 80, M: 90, L: 90
SEATPOST	Giant D-Fuse SL Offset 16mm
SADDLE	Liv Alacra SL
DRIVETRAIN	
SHIFTERS	Sram Rival AXS E1
FRONT DERAILLEUR	Sram Rival AXS E1
REAR DERAILLEUR	Sram Rival AXS E1, Max 36T
BRAKES	Sram Rival AXS E1 HRD, SRAM Paceline Rotors, [F]160, [R]160
BRAKE LEVERS	Sram Rival AXS E1 HRD
CASSETTE	Sram Rival, 12-speed, 10x36 XG-1250-D1
CHAIN	Sram Rival E1, 12-speed
CRANKSET	Sram Rival E1 DUB, 46/33 with power meter XXS: 160, XS: 165, S: 165, M: 170, L: 172.5
BOTTOM BRACKET	Sram DUB Press Fit

WHEELS	
RIMS	Giant SLR 1 40 Carbon Disc Wheel System
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	Giant Gavia Fondo 0 Tubeless, 700x32c (33.5mm effective), 170 TPI, Folding
EXTRAS	Computer mount, tubeless prepared, Bottle cages
LIMITS	
MAX TIRE CLEARANCE	700x40mm

Suggested Retail Price (CDN): \$6,699.00

FRAME GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	385	405	435	465	495
Seat Tube Angle	75.0°	74.5°	74.5°	74.0°	74.0°
Top Tube Length (mm)	500	520	525	535	555
Head Tube Length (mm)	110	125	145	165	185
Head Tube Angle	69.8°	71.0°	71.0°	71.0°	72.0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	76	68	68	68	61
Wheelbase (mm)	989	995	1002	1007	1013
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	73	73	73
Stack (mm)	510	528	547	566	589
Reach (mm)	363	373	373	373	381
Stand Over Height (mm)	683	712	737	762	789
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	165	165	170	170	172.5
Wheel Size	700C	700C	700C	700C	700C

All prices and specifications are subject to change without notice.