AVAIL ADVANCED PRO 1



ESPECIFICACIONES

CUADRO	
TALLAS	XXS, XS, S, M, L
COLORES	Dreamy Blue/Carbon/Chrome
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc
HORQUILLA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
MANILLAR	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
PUÑOS	Liv Stratus Elite 2.0
POTENCIA	Giant Contact SL AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
TIJA DE SILLÍN	Giant D-Fuse SL, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SILLÍN	Liv Alacra SL
TRANSMISIÓN	
MANETAS DE CAMBIO	SRAM Rival AXS E1
DESVIADOR	SRAM Rival AXS E1
CAMBIO TRASERO	SRAM Rival AXS E1
FRENOS	SRAM Rival E1 hydraulic, SRAM PaceLine rotors, [F] 160mm, [R] 140mm
PALANCAS DE FRENOS	SRAM Rival AXS E1
CASETTE	SRAM Rival E1, 12-speed, 10x36
CADENA	SRAM Rival E1
JGO. PLATOS Y BIELAS	SRAM Rival E1, 33/46 with Quark power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant SLR 1 40 WheelSystem, [F] 40mm, [R] 40mm
BUJES	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
RADIOS	Sapim CX-Ray
CUBIERTAS	Giant Gavia Fondo 0, tubeless, 700x32c, folding
EXTRAS	two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	40mm

Precio: 5.099,00 €

GEOMETRÍA

CUADRO	XXS	XS	S	M
Longitud del tubo del sillín (mm)	385	405	435	465
Ángulo del tubo del sillín	75,0°	74,5°	74,5°	74,0°
Longitud del tubo superior (mm) (mm)	500	520	525	535
Longitud del tubo de dirección (mm) (mm)	110	125	145	165
Ángulo del tubo de dirección	69,8°	71,0°	71,0°	71,0°
Inclinación de la horquilla (mm)	50	50	50	50
Trail (mm) (mm)	76,2	68,3	68,3	68,3
Distancia entre ejes (mm) (mm)	989	995	1002	1007
Longitud de la vaina (mm) (mm)	420	420	420	420
Caída del eje de pedalier (mm) (mm)	75	75	75	75
Stack (mm) (mm)	510	528	547	566
Stack (al manillar) (mm)	588	606	626	647
Reach (mm) (mm)	363	373	373	373
Reach (al manillar) (mm)	408	420	429	439
Altura del suelo al tubo (mm) (mm)	683	712	737	762
Ancho del manillar (mm) (mm)	380	380	400	400
Longitud de la potencia (mm) (mm)	70	70	80	90
Longitud de las bielas (mm) (mm)	160	165	165	170

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.