AVAIL ADVANCED PRO 1



SPECIFIKACIJE

OKVIR	
VELIČINE	XXS, XS, S, M, L
BOJE	Dreamy Blue/Carbon/Chrome
OKVIR	Advanced-grade composite, 12x142mm thru-axle, disc
VILICA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTE	
VOLAN	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
LULA VOLANA	Giant Contact SL AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
CIJEV SJEDALA	Giant D-Fuse SL, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SJEDALO	Liv Alacra SL
POGON	
RUČICE MJENJAČA	SRAM Rival AXS E1
PREDNJI MJENJAČ	SRAM Rival AXS E1
STRAŽNJI MJENJAČ	SRAM Rival AXS E1
KOČNICE	SRAM Rival E1 hydraulic, SRAM PaceLine rotors, [F] 160mm, [R] 140mm
RUČICE KOČNICA	SRAM Rival AXS E1
KAZETA	SRAM Rival E1, 12-speed, 10x36
LANAC	SRAM Rival E1
POGON	SRAM Rival E1, 33/46 with Quark power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant SLR 1 40 WheelSystem, [F] 40mm, [R] 40mm
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	Sapim CX-Ray
GUME	Giant Gavia Fondo 0, tubeless, 700x32c, folding
DODACI	two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dužina cijevi sjedala (mm)	385	405	435	465	495
Kut cijevi sjedala	75,0°	74,5°	74,5°	74,0°	74,0°
Dužina gornje cijevi (mm)	500	520	525	535	550
Dužina prednje cijevi (mm)	110	125	145	165	185
Kut vilice	69,8°	71,0°	71,0°	71,0°	72,0°
Zakrivljenost vilice (offset) (mm)	50	50	50	50	50
Staza (mm)	76,2	68,3	68,3	68,3	61,8
Međuosovinski razmak kotača (mm)	989	995	1002	1007	1013
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	420	420	420	420	420
Položaj osovine pogona (mm)	75	75	75	75	75
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	510	528	547	566	589
StackToHandlebar (mm)	588	606	626	647	668
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	363	373	373	373	381
ReachToHandlebar (mm)	408	420	429	439	449
Prekoračna visina (mm)	683	712	737	762	789
Širina volana (mm)	380	380	400	400	420
Dužina lule volana (mm)	70	70	80	90	90
Dužina poluge pedale (mm)	160	165	165	170	172,5

Sve navedene specifikacije podložne su promjeni bez prethodne najave.