AVAIL ADVANCED PRO 1



SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Golden Haze/Carbon/Chrome
FRAME	Advanced-grade composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-grade composite, full-composite OverDrive Aero steerer, stainless steel bearings 12x100mm, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Liv Contact SL D-Fuse, 31.8mm, 8-degree flare drop XXS: 410/380mm, XS: 410/380mm, S: 430/400mm, M: 430/400mm, L: 450/420mm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Contact SL AeroLight XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
ZADELPEN	Giant Contact SL D-Fuse, composite, -5/+15mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
ZADEL	Liv Alacra SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano 105 Di2
VOORDERAILLEUR	Shimano 105 Di2
ACHTERDERAILLEUR	Shimano 105 Di2
REMMEN	Shimano 105 Di2 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
REMHENDELS	Shimano 105 Di2 hydraulic
CASSETTE	Shimano 105, 12-speed, 11x36
AANDRIJVING	KMC X12
CRANKSET	Shimano 105, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Sapim
BANDEN	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRA'S	tubeless prepared, two bottle cages, 38mm max tire size, fender mount, computer mount

Adviesprijs: € 4.899,00

GEOMETRIE

FRAME	XS	S	M	L
Zitbuis lengte (mm)	405	435	465	495
Zitbuis hoek	74,5°	74,5°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	520	525	535	555
Balhoofdbuis Lengte (mm)	125	145	165	185
Balhoofdbuis Hoek	71,0°	71,0°	71,0°	72,0°
Vork Sprong (mm)	50	50	50	50
Naloop (mm)	68	68	68	61
Wielbasis (mm)	995	1002	1007	1013
Liggende achtervork lengte (mm)	420	420	420	420
Bottom Bracket Drop (mm)	75	73	73	73
Stack (mm)	528	547	566	589
Reach (mm)	373	373	373	381
Stand Over Height (mm)	712	737	762	789
Stuur breedte (mm)	380	400	400	420
Stuurpen Lengte (mm)	70	80	90	90
Cranklengte (mm)	165	170	170	172,5
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.