

AVAIL ADVANCED PRO 1



SPECS

RAMME	
STØRRELSE	XXS, XS, S, M, L
FARGE	Dreamy Blue/Carbon/Chrome
RAMME	Advanced-grade composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv Stratus Elite 2.0
STYRSTEM	Giant Contact SL AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SETEPINNE	Giant D-Fuse SL, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADEL	Liv Alacra SL
DRIVVERK	
GIRHENDLER	SRAM Rival AXS E1
FRONTGIR	SRAM Rival AXS E1
BAKGIR	SRAM Rival AXS E1
BREMSE	SRAM Rival E1 hydraulic, SRAM PaceLine rotors, [F] 160mm, [R] 140mm
BREMSEHENDLER	SRAM Rival AXS E1
KASSETT	SRAM Rival E1, 12-speed, 10x36
KJEDE	SRAM Rival E1
KRANK	SRAM Rival E1, 33/46 with Quark power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant SLR 1 40 WheelSystem, [F] 40mm, [R] 40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
EIKE	Sapim CX-Ray
DEKK	Giant Gavia Fondo 0, tubeless, 700x32c, folding
EXTRAS	two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size
LIMITS	
MAX TIRE CLEARANCE	40mm

GEOMETRI

RAMME	XXS	XS	S	M	L
Seat Tube Length (mm)	385	405	435	465	495
Seat Tube Angle	75,0°	74,5°	74,5°	74,0°	74,0°
Top Tube Length (mm)	500	520	525	535	550
Head Tube Length (mm)	110	125	145	165	185
Head Tube Angle	69,8°	71,0°	71,0°	71,0°	72,0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	76,2	68,3	68,3	68,3	61,8
Wheelbase (mm)	989	995	1002	1007	1013
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	75	75	75
Stack (mm)	510	528	547	566	589
StackToHandlebar (mm)	588	606	626	647	668
Reach (mm)	363	373	373	373	381
ReachToHandlebar (mm)	408	420	429	439	449
Stand Over Height (mm)	683	712	737	762	789
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	160	165	165	170	172,5

Alle spesifikasjonene kan endres uten varsel.