AVAIL ADVANCED PRO 1



SPECS

QUADRO	
TAMANHOS	XXS, XS, S, M, L
CORES	Dreamy Blue/Carbon/Chrome
QUADRO	Advanced-grade composite, 12x142mm thru-axle, disc
FORQUILHA	Advanced SL-grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
COMPONENTES	
GUIADOR	Liv Contact SL D-Fuse, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
PUNHOS	Liv Stratus Elite 2.0
AVANÇO	Giant Contact SL AeroLight, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
ESPIGÃO DE SELIM	Giant D-Fuse SL, composite, -5/+15mm offset, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SELIM	Liv Alacra SL
TRANSMISSÃO	
MANETES	SRAM Rival AXS E1
DESVIADOR DIANTEIRO	SRAM Rival AXS E1
DESVIADOR TRASEIRO	SRAM Rival AXS E1
TRAVÕES	SRAM Rival E1 hydraulic, SRAM PaceLine rotors, [F] 160mm, [R] 140mm
MANÍPULOS DOS TRAVÕES	SRAM Rival AXS E1
CASSETE	SRAM Rival E1, 12-speed, 10x36
CORRENTE	SRAM Rival E1
CONJUNTO PEDALEIRO	SRAM Rival E1, 33/46 with Quark power meter XXS: 160mm, XS: 165mm, S: 165mm, M: 170mm, L: 172.5mm
MOVIMENTO CENTRAL	SRAM DUB, press fit

RODAS	
AROS	Giant SLR 1 40 WheelSystem, [F] 40mm, [R] 40mm
CUBOS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
RAIOS	Sapim CX-Ray
PNEUS	Giant Gavia Fondo 0, tubeless, 700x32c, folding
EXTRAS	two bottle cage, fender mount, computer mount, tubeless prepared, 40mm max tire size
LIMITES	
FOLGA MÁXIMA DO PNEU	40mm

Preço: 4 499,00 €

GEOMETRIA

QUADRO	XXS	XS	S	M
Comprimento do tubo do assento (mm)	385	405	435	465
Ângulo do tubo do assento	75,0°	74,5°	74,5°	74,0°
Comprimento do tubo superior (mm)	500	520	525	535
Comprimento do tubo principal (mm)	110	125	145	165
Ângulo do tubo principal	69,8°	71,0°	71,0°	71,0°
Garfo ancinho (mm)	50	50	50	50
Trilha (mm)	76,2	68,3	68,3	68,3
distância entre eixos (mm)	989	995	1002	1007
Comprimento Chain Stay (mm)	420	420	420	420
Suporte inferior (mm)	75	75	75	75
Pilha (mm)	510	528	547	566
StackToHandlebar (mm)	588	606	626	647
Alcançar (mm)	363	373	373	373
ReachToHandlebar (mm)	408	420	429	439
Altura do standover (mm)	683	712	737	762
Largura do guidão (mm)	380	380	400	400
Comprimento da haste (mm)	70	70	80	90
Comprimento da Manivela (mm)	160	165	165	170

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.