AVAIL ADVANCED PRO 2 AXS



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Spectra
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced-Grade Composite, full-composite OverDrive 2 steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact SL D-Fuse, 31.8mm XXS:38cm, XS:38cm, S:40cm, M:40cm, L:42cm
GRIPS	Liv All Condition
STEM	Giant Contact SL XXS:70mm, XS:70mm, S:80mm, M:90mm, L:90mm
SEATPOST	Giant D-Fuse SL, composite, -5/+15mm offset XXS:350mm, XS:350mm, S:350mm, M:350mm, L:350mm
SADDLE	Liv Alacra SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Rival eTap AXS
FRONT DERAILLEUR	SRAM Rival eTap AXS
REAR DERAILLEUR	SRAM Rival eTap AXS
BRAKES	SRAM Rival eTap hydraulic, SRAM PaceLine rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Rival hydraulic
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAIN	SRAM Rival D1
CRANKSET	SRAM Rival D1 DUB, 33/46 with Giant Halo PowerPro power meter
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 2 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
HUBS	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Sprint
TIRES	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	tubeless prepared, 35mm max tire size

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	385	400	435	470	505
Seat Tube Angle	75,0°	74,5°	74,5°	74,0°	74,0°
Top Tube Length (mm)	500	515	525	540	555
Head Tube Length (mm)	110	125	145	165	185
Head Tube Angle	70,0°	70,5°	71,5°	72,0°	72,0°
Fork Rake (mm)	50	50	50	50	50
Trail (mm)	74,5	71,3	64,7	61,5	61,5
Wheelbase (mm)	988	995	998	1004	1020
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	75	75	73	73	73
Stack (mm)	511	527	547	568	587
Reach (mm)	363	368	373	377	387
Stand Over Height (mm)	672	684	716	745	772
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	165	165	170	170	172,5
Wheel Size	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.