

# AVAIL ADVANCED PRO 2



## SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Carbon/Airglow
FRAME	Advanced-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced-Grade Composite, full-composite OverDrive 2 steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Contact SL D-Fuse, 31.8mm XS:38cm, S:40cm, M:40cm
GRIPS	Liv All Condition
STEM	Giant Contact SL XS:70mm, S:80mm, M:90mm
SEATPOST	Giant D-Fuse SL, composite, -5/+15mm offset
SADDLE	Liv Alacra SL CS
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano 105 Di2
FRONT DERAILLEUR	Shimano 105 Di2
REAR DERAILLEUR	Shimano 105 Di2
BRAKES	Shimano 105 hydraulic, Shimano RT-70 rotors [F]160mm, [R]140mm
BRAKE LEVERS	Shimano 105 Di2
CASSETTE	Shimano Di2, 12-speed, 11x34
CHAIN	KMC X12
CRANKSET	Shimano 105, 34/50 XS:165mm, S:170mm, M:170mm
BOTTOM BRACKET	Shimano, press fit

WHEELS	
RIMS	Giant SLR 2 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
HUBS	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl driver, CenterLock, 12mm thru-axle
SPOKES	Sapim Sprint
TIRES	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	Tubeless prepared, 35mm max tyre size

Price: \$5,499 RRP

## GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	400	435	470
Seat Tube Angle	74.5°	74.5°	74.0°
Top Tube Length (mm)	515	525	540
Head Tube Length (mm)	125	145	165
Head Tube Angle	70.5°	71.5°	72.0°
Fork Rake (mm)	50	50	50
Trail (mm)	71.3	64.7	61.5
Wheelbase (mm)	995	998	1004
Chain Stay Length (mm)	420	420	420
Bottom Bracket Drop (mm)	75	73	73
Stack (mm)	527	547	568
Reach (mm)	368	373	377
Stand Over Height (mm)	684	716	745
Stem Length (mm)	70	80	90
Crank Length (mm)	165	170	170
Wheel Size	700C	700C	700C

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.