



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XXS, XS, S, M, L
ЦВЯТ	Sandshell/Cold Night
РАМКА	ALUXX-grade aluminum, 12x142mm thru-axle, disc
ВИЛКА	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
ЗАДЕН АМОРТИСЬОР	N/A
КОМПОНЕНТИ	
КОРМИЛО	Liv D-Fuse SL, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
ГРИПОВЕ	Liv All Condition
ЛАПА	Giant Contact, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
КОЛЧЕ ЗА СЕДАЛКА	Giant D-Fuse, composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
СЕДАЛКА	Liv Approach
DRIVETRAIN	
КОМАНДИ	Shimano 105
ПРЕДЕН ДЕРАЙЛЪОР	Shimano 105
ЗАДЕН ДЕРАЙЛЪОР	Shimano 105
СПИРАЧКИ	Shimano 105 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano 105
КАСЕТА	Shimano 105, 12-speed, 11x36
ВЕРИГА	KMC X12
КУРБЕЛ	Shimano 105, 34/50, XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
СРЕДНА КАСЕТА	Shimano BB-RS501

КАПЛИ	
ШИНИ	Giant P-R2 Disc, alloy
ГЛАВИНИ	Giant alloy, 12mm thru-axle
СПИЦИ	Sapim
ГУМИ	Giant Gavia Fondo 2, 700x32c, tubeless
ЕКСТРИ	tubeless prepared, 38mm max tire size
ЛИМИТИ	
MAX TIRE CLEARANCE	38mm

ГЕОМЕТРИЯ

РАМКА	XXS	XS	S	M	L
Seat Tube Length (mm)	395	430	465	500	535
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	74,0°
Top Tube Length (mm)	500	515	525	540	555
Head Tube Length (mm)	120	135	150	170	190
Head Tube Angle	70,0°	70,5°	72,0°	72,0°	72,0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	76,2	73	63,5	63,5	63,5
Wheelbase (mm)	986	998	990	1000	1016
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	70	70	70	70	70
Stack (mm)	514	530	550	569	588
Обсер (mm)	362	372	372	377	386
Stand Over Height (mm)	662	687	716	744	772
Ширина на Кормило (mm)	380	380	400	400	420
Дължина на Лапа (mm)	70	70	80	90	90
Дължина на Курбел (mm)	160	165	165	170	172,5

All specifications listed are subject to change without notice.