



SPECS

FRAME	
SIZES	XS, S, M
COLOURS	Sandshell/Cold Night
FRAME	ALUXX-grade aluminium, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv D-Fuse SL, 31.8mm XS:38cm, S:40cm, M:40cm
GRIPS	Liv All Condition
STEM	Giant Contact XS:70mm, S:80mm, M:90mm
SEATPOST	Giant D-Fuse, composite, 14mm offset
SADDLE	Liv Approach
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BRAKE LEVERS	Shimano 105
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12
CRANKSET	Shimano 105, 34/50 XS:165mm, S:170mm, M:170mm
BOTTOM BRACKET	Shimano BB-RS501

WHEELS	
RIMS	Giant P-R2, [F]30mm, [R]30mm
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 2, 700x32c, tubeless
EXTRAS	Tubeless prepared, 38mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	38mm

Price: \$2,699.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	430	465	500
Seat Tube Angle	75.0°	74.5°	74.0°
Top Tube Length (mm)	515	525	540
Head Tube Length (mm)	135	150	170
Head Tube Angle	70.5°	72.0°	72.0°
Fork Rake (mm)	45	45	45
Trail (mm)	73	63.5	63.5
Wheelbase (mm)	998	990	1000
Chain Stay Length (mm)	420	420	420
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	530	550	569
Reach (mm)	372	372	377
Stand Over Height (mm)	687	716	744
Stem Length (mm)	70	80	90
Crank Length (mm)	165	170	170

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.