



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Al Blue
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv D-Fuse SL, 31.8mm XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SEATPOST	Giant Contact D-Fuse, composite, 14mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADDLE	Liv Approach
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 hydraulic, Shimano rotors [F]160mm, [R]160mm
BRAKE LEVERS	Shimano 105 GS
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12
CRANKSET	Shimano FC-RS520, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	cartridge

WHEELS	
RIMS	Giant P-R2 Disc wheelset, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 2, 700x32c, tubeless
EXTRAS	tubeless prepared, 38mm max tire size

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	375	410	445	480	515
Seat Tube Angle	75,0°	74,5°	74,5°	74,0°	74,0°
Top Tube Length (mm)	502	515	525	540	555
Head Tube Length (mm)	103	118	138	158	178
Head Tube Angle	70,0°	70,5°	71,5°	72,0°	72,0°
Fork Rake (mm)	53	53	53	53	53
Trail (mm)	72,8	69,5	62,9	59,6	59,6
Wheelbase (mm)	994	999	1001	1006	1022
Chain Stay Length (mm)	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80
Stack (mm)	522	538	561	582	601
Reach (mm)	362	366	369	373	383
Stand Over Height (mm)	653	681	709	736	766
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	165	165	170	170	172,5
Wheel Size	700C	700C	700C	700C	700C

All specifications listed are subject to change without notice.