



SPECS

RAMME	
STØRRELSE	XXS, XS, S, M, L
FARGE	Al Blue
RAMME	ALUXX-grade aluminum, 12x142mm thru-axle, disc
GAFFEL	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
DEMPER	N/A
KOMPONENTER	
STYRE	Liv D-Fuse SL, 31.8mm XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv All Condition
STYRSTEM	Giant Contact XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SETEPINNE	Giant Contact D-Fuse, composite, 14mm offset XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADEL	Liv Approach
PEDALER	N/A
DRIVVERK	
GIRHENDLER	Shimano 105
FRONTGIR	Shimano 105
BAKGIR	Shimano 105
BREMSER	Shimano 105 hydraulic, Shimano rotors [F]160mm, [R]160mm
BREMSEHENDLER	Shimano 105 GS
KASSETT	Shimano 105, 12-speed, 11x36
KJEDE	KMC X12
KRANK	Shimano FC-RS520, 34/50 XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	cartridge

HJUL	
FELG	Giant P-R2 Disc wheelset, alloy
NAV	Giant alloy, 12mm thru-axle
EIKE	Sapim
DEKK	Giant Gavia Fondo 2, 700x32c, tubeless
EXTRAS	tubeless prepared, 38mm max tire size

GEOMETRI

RAMME	XXS	XS	S	M	L
Seat Tube Length (mm)	375	410	445	480	515
Seat Tube Angle	75,0°	74,5°	74,5°	74,0°	74,0°
Top Tube Length (mm)	502	515	525	540	555
Head Tube Length (mm)	103	118	138	158	178
Head Tube Angle	70,0°	70,5°	71,5°	72,0°	72,0°
Fork Rake (mm)	53	53	53	53	53
Trail (mm)	72,8	69,5	62,9	59,6	59,6
Wheelbase (mm)	994	999	1001	1006	1022
Chain Stay Length (mm)	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80
Stack (mm)	522	538	561	582	601
Reach (mm)	362	366	369	373	383
Stand Over Height (mm)	653	681	709	736	766
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	165	165	170	170	172,5
Wheel Size	700C	700C	700C	700C	700C

Alle spesifikasjonene kan endres uten varsel.