



SPECS

FRAME	
SIZES	XXS, XS, S, M, L
COLORS	Sandshell/Cold Night
FRAME	ALUXX-grade aluminum, 12x142mm thru-axle, disc
FORK	Advanced-grade composite, full-composite OverDrive steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv D-Fuse SL, 31.8mm, XXS: 380mm, XS: 380mm, S: 400mm, M: 400mm, L: 420mm
GRIPS	Liv All Condition
STEM	Giant Contact, XXS: 70mm, XS: 70mm, S: 80mm, M: 90mm, L: 90mm
SEATPOST	Giant D-Fuse, composite, XXS: 350mm, XS: 350mm, S: 350mm, M: 350mm, L: 350mm
SADDLE	Liv Approach
DRIVETRAIN	
SHIFTERS	Shimano 105
FRONT DERAILLEUR	Shimano 105
REAR DERAILLEUR	Shimano 105
BRAKES	Shimano 105 hydraulic, Giant MPH rotors, [F]160mm, [R]160mm
BRAKE LEVERS	Shimano 105
CASSETTE	Shimano 105, 12-speed, 11x36
CHAIN	KMC X12
CRANKSET	Shimano 105, 34/50, XXS: 165mm, XS: 165mm, S: 170mm, M: 170mm, L: 172.5mm
BOTTOM BRACKET	Shimano BB-R5501

WHEELS	
RIMS	Giant P-R2 Disc, alloy
HUBS	Giant alloy, 12mm thru-axle
SPOKES	Sapim
TIRES	Giant Gavia Fondo 2, 700x32c, tubeless
EXTRAS	tubeless prepared, 38mm max tire size
LIMITS	
MAX TIRE CLEARANCE	38mm

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	395	430	465	500	535
Seat Tube Angle	75,0°	75,0°	74,5°	74,0°	74,0°
Top Tube Length (mm)	500	515	525	540	555
Head Tube Length (mm)	120	135	150	170	190
Head Tube Angle	70,0°	70,5°	72,0°	72,0°	72,0°
Fork Rake (mm)	45	45	45	45	45
Trail (mm)	76,2	73	63,5	63,5	63,5
Wheelbase (mm)	986	998	990	1000	1016
Chain Stay Length (mm)	420	420	420	420	420
Bottom Bracket Drop (mm)	70	70	70	70	70
Stack (mm)	514	530	550	569	588
Reach (mm)	362	372	372	377	386
Stand Over Height (mm)	662	687	716	744	772
Handlebar Width (mm)	380	380	400	400	420
Stem Length (mm)	70	70	80	90	90
Crank Length (mm)	160	165	165	170	172,5

All specifications listed are subject to change without notice.