

AVAIL AR 4



SPECIFICATIES

FRAME	
MATEN	XXS, XS, S, M, L
KLEUREN	Snow Drift/Silver
FRAME	ALUXX-Grade Aluminum, 12x142mm thru-axle, disc
VOORVORK	Advanced-Grade Composite, full-composite OverDrive steerer, 12x100mm, disc
DEMPER	N/A
ONDERDELEN	
STUUR	Liv Connect, 31.8mm XXS:38cm, XS:38cm, S:40cm, M:40cm, L:42cm
HANDVATTEN	Liv All Condition
STUURPEN	Giant Sport XXS:70mm, XS:70mm, S:80mm, M:90mm, L:90mm
ZADELPEEN	Giant D-Fuse, alloy XXS:350mm, XS:350mm, S:350mm, M:350mm, L:350mm
ZADEL	Liv Approach
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano Claris
VOORDERAILLEUR	Shimano Claris
ACHTERDERAILLEUR	Shimano Claris
REMMEN	Tektro MD-C550 mechanical, Shimano rotors [F]160mm, [R]160mm
REMHENDELS	Shimano Claris
CASSETTE	Shimano CS-HG50, 8-speed, 11x34
AANDRIJVING	KMC Z83
CRANKSET	FSA Tempo, 34/50 XXS:165mm, XS:165mm, S:170mm, M:170mm, L:172.5mm
BOTTOM BRACKET	cartridge

WIELSET	
VELGEN	Giant S-R2 Disc wheelset
NAVEN	Giant S-R2 Disc wheelset
SPAKEN	Giant S-R2 Disc wheelset
BANDEN	Giant S-R3 AC, 700x32c
EXTRA'S	38mm max tire size

Adviesprijs: € 1.099,00

GEOMETRIE

FRAME	XXS	XS	S	M	L
Zitbuis lengte (mm)	375	410	445	480	515
Zitbuis hoek	75,0°	74,5°	74,5°	74,0°	74,0°
Frame Lengte (horizontaal) (mm)	502	515	525	540	555
Balhoofdbuis Lengte (mm)	103	118	138	158	178
Balhoofdbuis Hoek	70,0°	70,5°	71,5°	72,0°	72,0°
Vork Sprong (mm)	53	53	53	53	53
Naloop (mm)	72,8	69,5	62,9	59,6	59,6
Wielbasis (mm)	994	999	1001	1006	1022
Liggende achtersvork lengte (mm)	422	422	422	422	422
Bottom Bracket Drop (mm)	80	80	80	80	80
Stack (mm)	522	538	561	582	601
Reach (mm)	362	366	369	373	383
Stand Over Height (mm)	653	681	709	736	766
Stuur breedte (mm)	380	380	400	400	420
Stuurpen Lengte (mm)	70	70	80	90	90
Cranklengte (mm)	165	165	170	170	172,5
Wielmaat	700C	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.