

AVOW ADVANCED PRO 1



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M
ЦВЯТ	Terracotta/Carbon
РАМКА	Advanced-Grade Composite
ВИЛКА	Advanced-Grade Composite, alloy OverDrive steerer
ЗАДЕН АМОРТИСЬОР	N/A
КОМПОНЕНТИ	
КОРМИЛО	Liv Avow Carbon XXS:36cm, XS:36cm, S:38cm, M:40cm, L:42cm
ГРИПОВЕ	Liv Contact Gel
ЛАПА	Liv Avow Alloy XS:80mm, S:90mm, M:100mm,
КОЛЧЕ ЗА СЕДАЛКА	Liv Avow Carbon XS:TKmm, S:TKmm, M:TKmm,
СЕДАЛКА	ISM PS1.0
ПЕДАЛИ	N/A
DRIVETRAIN	
КОМАНДИ	Shimano Ultegra Di2 ST-R8170
ПРЕДЕН ДЕРАЙЛЪОР	Shimano Ultegra Di2 FD-R8150
ЗАДЕН ДЕРАЙЛЪОР	Shimano Ultegra Di2 RD-R8150
СПИРАЧКИ	Giant SpeedControl SL
РЪКОХВАТКИ ЗА СПИРАЧКИ	Giant Trinity
КАСЕТА	Shimano Ultegra, 12-speed, 11x30
ВЕРИГА	Shimano Ultegra
КУРБЕЛ	Shimano Ultegra, 36/52 XS:160mm, S:165mm, M:165mm
СРЕДНА КАСЕТА	Shimano, press fit

КАПЛИ	
ШИНИ	Giant P-A2 wheelset
ГЛАВИНИ	Giant P-A2 wheelset
СПИЦИ	Giant P-A2 wheelset
ГУМИ	Giant Gavia AC Lite, tubeless, 700x25c (26.5mm), folding
ЕКСТРИ	integrated hydration, integrated food storage, misc fairings, AeroVault System, 25mm max tire size

ГЕОМЕТРИЯ

РАМКА	XXS	XS	S	M
Seat Tube Length (mm)	450	480	510	530
Seat Tube Angle	77,0°	77,0°	77,0°	77,0°
Top Tube Length (mm)	480	500	515	540
Head Tube Length (mm)	80	80	95	125
Head Tube Angle	71,5°	72,0°	72,5°	72,5°
Fork Rake (mm)	40	40	40	40
Trail (mm)	62	68	64	64
Wheelbase (mm)	949	961	974	1001
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	64	75	75	75
Stack (mm)	442	490	504	534
Обсер (mm)	378	387	398	417
Stand Over Height (mm)	708	740	767	788
Ширина на Кормило (mm)	400	400	400	400
Дължина на Лапа (mm)	80	80	80	80
Дължина на Курбел (mm)	160	165	165	165
Размер на Каплите	700C	700C	700C	700C

All specifications listed are subject to change without notice.